



Packing what?	Nail box: can be on the machine specifications Size: length 20mm-100mm nails
which way Packing	Box, box shape suggestions (L*W*H) 220mm*100mm*60mm
Magnetic sorting machine	Iron nails with a length greater than 60mm need to be sorted by magnetic sorting machine (double-sided magnet)
Automatic box opening and sealing	Automatic box opening machine and automatic box sealing machine are purchased equipment, it is recommended that customers fold boxes and cover boxes themselves

2024-2-2




Name	Nails Specification range: Length 20mm-100mm nails	
form of measurement	Weighing + fiber count complement	
Speed	Single weighing + single feeding 5-6 boxes/min or so	
Packing way	Packing (single variety multi-quantity packing)	
Box shape	Customer box shape can be changed to suggest using a tilting bottom carton	
Packing weight	The machine can be used: 1KG~5KG/ box;	
Box size	suggest box size (L*W*H) : 220mm* 100mm*60mm	
Voltage/power	Machines can be manufactured according to the customer's local voltage and power	
Optional equipment	Automatic box opening machine, automatic box sealing machine (this equipment is purchased equipment, it is recommended to manually fold the box and cover the box)	





Equipment diagram (excluding automatic box opening machine and automatic box sealing machine)






Previous packing machine sample (for reference only)






Electro nic control main engine




Magnetic hoist

vibrating
feeder
Boat type bucket elevator

-U-shaped conveyor line








Includes PLC program, man-machine interface

Brand: Delta


Functions: switch, emergency stop, parameter

setting, quantity adjustment, etc.



Ship type bucket elevator (optional), vibration hopper












- 1, ship type bucket elevator: optional device to flip the material to lift into the vibration hopper, there is a truss crane can not be used, optional device
- 2, vibration hopper: can hold 300-500KG material


2024年2月2日




Magnetic hoist, weighing mechanism

Magnetic hoist





Weighing mechanism





- The weighing system consists of three modules: one vibrating hopper, one magnetic hoist and one weighing box.
- Operation process: the direct vibration system (vibration storage hopper) feeds to the magnetic elevator, the magnetic elevator will send the product to the weighing box, when the weighing box is fed to the required amount of 90% to 95%, the elevator stops feeding, measured the exact amount, and the vibrating disk is filled by counting








Therearetwomaincountingmodesofvibrationdisc, trackmode, boxmode and belt linemode. Trackmode: mainly used for screw products; This equipmet is equipped with a 620 mms crew plate; Boxmode: mainly used for granular products, such as gaskets, nuts, etc.

countingmethodsareusingopticalfbercounting, the use of op TExbrand optical fiber in Japan, can deal with various shapes of materials, and can automatically correct the impact of dust on the brightness value.

V

Equipment composition - magnetic sorting machine



Nails more than 50mm in length need to be sorted, and the sorting effect is about 70%





Accessories name	Brand	
Power switch	Schneider	
button	Schneider	
PLC	Delta	
touch screen	Delta	
relay	OMRO	
solid state relay	Delixi	
air cylinder	AIRTAC	
Counter cylinder	SMC	
temperature-controlled meter	SHANGHAI YATAI	
motor	Taibang/Shengbang	
bearing	NSK (important)	
inverter	delta	
counting sensor	OPTEX	
pressure sensor	Mettler Toledo	
connector plug	豪光	