



MINIMUM WATER FLOW 19L/MIN
 MAXIMUM WATER PRESSURE
 40 PSI (2.7 BAR)

6 HOLES 18 DIA SPACED
 AS SHOWN ON 445 DCD

WATER INLET 1/2" NPT (MALE)
 PIPE BRAKE AS SHOWN

WATER OUTLET 1/2" BSP (MALE)
 1/2" BSP BARREL NIPPLE FOR
 CONNECTING TO FLEXIBLE HOSE
 WATER OUTLET TO BE AT TOP
 OF BRAKE TO ENSURE THAT
 BRAKE IS COMPLETELY FULL OF WATER.

5	WAS	30-7-84	MR
4	WAS	31-3-84	MR
3	WAS	10-3-84	MR
2	WAS	10-3-84	MR
1	WAS	10-3-84	MR

TITLE		SCALE	
ASS BRAKE CSM 114		1/2	
TOTAL WEIGHT OF ASSEMBLY	138 kg	TOTAL ASSEMBLY - INERTIA (J)	0.013 kgm ²
HUB AND CENTRE PLATE - WEIGHT	kg	HUB AND CENTRE PLATE - INERTIA (J)	kgm ²
DRIVING RING AND DISC - WEIGHT	kg	DRIVING RING AND DISC - INERTIA (J)	kgm ²

WICHITA

Wichita Co. Ltd
 Ampleford Road
 Bedford, MK42 0PD, England
 Telephone: 0234-28811
 Telex: 82283

THIS DRAWING MUST NOT BE COPIED IN WHOLE OR PART WITHOUT WRITTEN PERMISSION

MODEL BEST N° MODÈLE		
BRAKE BREMSE FREIN		
CSM 114 - COPPER / AI-13		
DRAWN	REC	CHECKED
DATE 15-6-79	DATE	DATE 15-6-79
QTY. ASSY ORG.	OLD PART No.	SERIAL No.
6125		
DRG. No. 75114-070		