

4axis cnc lathe spindle speed 6000 rpm subspindle speed 3000 rpm
Programable tailstock 50mm Max cutting diameter 500mm Max cutting length 1000mm Chuck size 250mm
Live tools 6pcs 12 position turret 4 pcs angular milling holders tool presetter Automatic bar fider
3000mm wirh 12pcs collet can be change with chuck Screw type chip convaier Fanuc control Weight aprox 5000 kg

LOTO FABRICATION PUMA 10 - N°301

Sample Control Panel



Création: F.CORREIA 14/01/2016
Révision:

DE TRAVAIL

VUE GENERALE DE L'EQUIPEMENT

RÈGLES DE CONSIDÉRATION D'UNE INSTALLATION		MESH
1.1.1.1	1.1.1.2	1.1.1.3
1.1.1.4	1.1.1.5	1.1.1.6
1.1.1.7	1.1.1.8	1.1.1.9
1.1.1.10	1.1.1.11	1.1.1.12
1.1.1.13	1.1.1.14	1.1.1.15
1.1.1.16	1.1.1.17	1.1.1.18
1.1.1.19	1.1.1.20	1.1.1.21
1.1.1.22	1.1.1.23	1.1.1.24
1.1.1.25	1.1.1.26	1.1.1.27
1.1.1.28	1.1.1.29	1.1.1.30
1.1.1.31	1.1.1.32	1.1.1.33
1.1.1.34	1.1.1.35	1.1.1.36
1.1.1.37	1.1.1.38	1.1.1.39
1.1.1.40	1.1.1.41	1.1.1.42
1.1.1.43	1.1.1.44	1.1.1.45
1.1.1.46	1.1.1.47	1.1.1.48
1.1.1.49	1.1.1.50	1.1.1.51
1.1.1.52	1.1.1.53	1.1.1.54
1.1.1.55	1.1.1.56	1.1.1.57
1.1.1.58	1.1.1.59	1.1.1.60
1.1.1.61	1.1.1.62	1.1.1.63
1.1.1.64	1.1.1.65	1.1.1.66
1.1.1.67	1.1.1.68	1.1.1.69
1.1.1.70	1.1.1.71	1.1.1.72
1.1.1.73	1.1.1.74	1.1.1.75
1.1.1.76	1.1.1.77	1.1.1.78
1.1.1.79	1.1.1.80	1.1.1.81
1.1.1.82	1.1.1.83	1.1.1.84
1.1.1.85	1.1.1.86	1.1.1.87
1.1.1.88	1.1.1.89	1.1.1.90
1.1.1.91	1.1.1.92	1.1.1.93
1.1.1.94	1.1.1.95	1.1.1.96
1.1.1.97	1.1.1.98	1.1.1.99
1.1.1.100	1.1.1.101	1.1.1.102



ATIFICATION DES DISPOSITIFS D'ISOLATION D'ENERGIE







