



## FTL/S19-25-32型气动捆扎分体式

### FTL/S19-25-32 Pneumatic Strapping Split Type

|                                     |  |
|-------------------------------------|--|
| 使用气压<br>Air pressure                | 0.49~0.63Mpa   |
| 空载钢带速度<br>Steel strip tension speed | 85mm/sec   |
| 拉紧力<br>Tension force                | 8.5KN  |
| 拉紧机重量<br>Tensioning tool weight     | 4.1kg  |
| 锁扣机重量<br>Sealing tool weight        | 3.1kg  |
| 钢带规格<br>Straps specification        | 宽度19-32mm, 厚度0.8-1.2mm<br>Width: 19-32mm, thickness: 0.8-1.2mm |
| 双夹口承受拉力<br>Strength of extension    | 15KN   |



## KZ-32/19 型气动捆扎机

### KZ-32/19 Pneumatic Steel Strapping Tools

|   |                      |
|---|----------------------|
| 捆带材质<br>Apply straps                              | 钢带 Steel strip       |
| 使用空气压力<br>Air pressure                            | 0.35-0.6 Mpa         |
| 使用捆带规格<br>Straps specification                    | (19-32)x(0.8-1.2) mm |
| 钢带拉紧速度<br>Steel strip tension speed               | 5.3 m/min            |
| 拉紧力<br>Tension force                              | ≥9.8kN/0.6Mpa        |
| 锁扣部分抗拉强度<br>Extension strength of padlock section | ≥18.4 kN             |
| 整机重量<br>Machine weight                            | 15 kg                |

