

Add: 3 North Tieling Road, Minhou, Fuzhou, Fujian, 350101, P.R.China

Phone: +86 (591) 2262 8228

Fax: +86 (591) 2207 9666

E-mail: info@fjqj.com

Item

Sl. No.	Item Description	Unit	Net Reqr. Qty.	UNIT PRICE USD	AMOUNT USD
1	<p><u>MIXING CHEST AGITATOR</u> <u>Requirements</u> Tag no.: 410 A 041 & 042 Type: Side entry / horizontal Nominal volume: 200m3 Chest material: concrete – tile lined Chest dimensions: L=10000mm ; W=4000mm ; H=5000mm Suspension: bagasse slurry with consistency 2.5-3.0% / temp. 30-50°C / pH 4 to 6 Material: S.S.316 for part in contact with pulp</p> <p><u>Specification</u> Model: ZTMX10 Impeller type: 3 blades Impeller diameter: Φ 1000mm Seal form: packing water seal Seal water pressure: 0.3-0.5 Mpa Seal water flow: 2.5L/min Driving type: V-belt driving Motor: 22KW/6P – 380V – 50Hz – B3 Scope: complete agitator including motor</p>	unit			
	<p>Material specification for agitator Main shaft is made in tempered by 40Cr steel Protective shaft sleeve is made in stainless steel SS304 Bearing housing is made in HT250 cast iron Flange for vat connecting are made in stainless steel SS304 / Drive and driven pulleys are made in HT250 cast iron</p>				