
	Eslam Abad Gharb(NPC) Gas To Methanol and PVM Complex				
Page	MATERIAL DATA SHEET FOR CATALYST TUBES		Rev.	Class	
1 of 5	GTP-VD-10-20-ME-DSH-SH504		D0	B	
<h1>MATERIAL DATA SHEET FOR CATALYST TUBES</h1>					
					<i>E. FORMILI</i>
D0	2-May-2023	Issued for Information	E.F.	S.CH.	E.F.
Rev.	Issue Date	Purpose of Issue	Prepared	Checked	Approved

Eslam Abad Gharb(NPC)
 Gas To Methanol and PVM Complex



Page	MATERIAL DATA SHEET FOR CATALYST TUBES	Rev.	Class
2 of 5	GTP-VD-10-20-ME-DSH-SH504	D0	B

TABULATION OF REVISED PAGES




Page	Revision				
	D0				
1	X				
2	X				
3	X				
4	X				
5	X				
6					
7					
8					
9					
10					
11					
12					
13					
14					
15					
16					
17					
18					
19					
20					
21					
22					
23					
24					
25					
26					
27					
28					
29					
30					






Page	Revision				
31					
32					
33					
34					
35					
36					
37					
38					
39					
40					
41					
42					
43					
44					
45					
46					
47					
48					
49					
50					
51					
52					
53					
54					
55					
56					
57					
58					
59					
60					

Page	Revision				
61					
62					
63					
64					
65					
66					
67					
68					
69					
70					
71					
72					
73					
74					
75					
76					
77					
78					
79					
80					
81					
82					
83					
84					
85					
86					
87					
88					
89					
90					

	ESLAM ABAD GHARB GAS TO METHANOL AND PVM PLANT		
Page	MATERIAL DATA SHEET FOR CATALYST TUBES	Rev.	Class
3 of 5	GTP-VD-10-20-ME-DSH-SH504	D0	B


1 of 3	P1003-MEC-MDS-1001	1.0	---
--------	--------------------	-----	-----

1	Project No23057 (NH25-35MIC)																																																																			
2	<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td data-bbox="446 593 726 638" style="text-align: center;">  Qingdao NPA Industry Co., Ltd </td> <td data-bbox="726 593 925 638" style="text-align: center;"> Material Data Sheet NH25-35MIC </td> <td data-bbox="925 593 1133 638" style="text-align: center;"> Doc. No: NH25-35MIC Rev.: 01 </td> </tr> </table>					 Qingdao NPA Industry Co., Ltd	Material Data Sheet NH25-35MIC	Doc. No: NH25-35MIC Rev.: 01																																																												
 Qingdao NPA Industry Co., Ltd	Material Data Sheet NH25-35MIC	Doc. No: NH25-35MIC Rev.: 01																																																																		
3																																																																				
4	Alloy: NH25-35MIC																																																																			
5	Service: Centricast tubes sections																																																																			
6	Reducer section (Static cast)																																																																			
7	Grid plate (Static cast)																																																																			
8																																																																				
9	1. Chemical Analysis As Shown																																																																			
10	<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th data-bbox="446 817 622 840">Element</th> <th data-bbox="622 817 861 840">Mini-Max</th> <th data-bbox="861 817 1133 840">Remarks</th> </tr> </thead> <tbody> <tr><td data-bbox="446 840 622 862">C</td><td data-bbox="622 840 861 862">0.35-0.45</td><td data-bbox="861 840 1133 862"></td></tr> <tr><td data-bbox="446 862 622 884">Mn</td><td data-bbox="622 862 861 884">≤1.25</td><td data-bbox="861 862 1133 884"></td></tr> <tr><td data-bbox="446 884 622 907">Si</td><td data-bbox="622 884 861 907">0.75-1.5</td><td data-bbox="861 884 1133 907"></td></tr> <tr><td data-bbox="446 907 622 929">S</td><td data-bbox="622 907 861 929">≤0.03</td><td data-bbox="861 907 1133 929"></td></tr> <tr><td data-bbox="446 929 622 952">P</td><td data-bbox="622 929 861 952">≤0.03</td><td data-bbox="861 929 1133 952"></td></tr> <tr><td data-bbox="446 952 622 974">Cr</td><td data-bbox="622 952 861 974">24.0-28.0</td><td data-bbox="861 952 1133 974"></td></tr> <tr><td data-bbox="446 974 622 996">Ni</td><td data-bbox="622 974 861 996">32.0-36.0</td><td data-bbox="861 974 1133 996"></td></tr> <tr><td data-bbox="446 996 622 1019">Nb</td><td data-bbox="622 996 861 1019">0.7-1.6</td><td data-bbox="861 996 1133 1019"></td></tr> <tr><td data-bbox="446 1019 622 1041">Ti</td><td data-bbox="622 1019 861 1041">0.05-0.25</td><td data-bbox="861 1019 1133 1041"></td></tr> <tr><td data-bbox="446 1041 622 1064">Pb</td><td data-bbox="622 1041 861 1064">≤0.01</td><td data-bbox="861 1041 1133 1064"></td></tr> <tr><td data-bbox="446 1064 622 1086">Sn</td><td data-bbox="622 1064 861 1086">≤0.01</td><td data-bbox="861 1064 1133 1086"></td></tr> <tr><td data-bbox="446 1086 622 1108">Zr</td><td data-bbox="622 1086 861 1108">0.01-0.25</td><td data-bbox="861 1086 1133 1108"></td></tr> <tr><td data-bbox="446 1108 622 1131">Fe</td><td data-bbox="622 1108 861 1131">Balance</td><td data-bbox="861 1108 1133 1131"></td></tr> <tr><td data-bbox="446 1131 622 1153">Mo</td><td data-bbox="622 1131 861 1153">≤0.5</td><td data-bbox="861 1131 1133 1153"></td></tr> <tr><td data-bbox="446 1153 622 1176">Cu</td><td data-bbox="622 1153 861 1176">≤0.25</td><td data-bbox="861 1153 1133 1176"></td></tr> <tr><td data-bbox="446 1176 622 1198">As</td><td data-bbox="622 1176 861 1198">≤0.01</td><td data-bbox="861 1176 1133 1198"></td></tr> <tr><td data-bbox="446 1198 622 1220">V</td><td data-bbox="622 1198 861 1220">≤0.10</td><td data-bbox="861 1198 1133 1220"></td></tr> <tr><td data-bbox="446 1220 622 1243">Al</td><td data-bbox="622 1220 861 1243">≤0.05</td><td data-bbox="861 1220 1133 1243"></td></tr> <tr><td data-bbox="446 1243 622 1265">W</td><td data-bbox="622 1243 861 1265">≤0.30</td><td data-bbox="861 1243 1133 1265"></td></tr> <tr><td data-bbox="446 1265 622 1288">Zn</td><td data-bbox="622 1265 861 1288">≤0.01</td><td data-bbox="861 1265 1133 1288"></td></tr> </tbody> </table>					Element	Mini-Max	Remarks	C	0.35-0.45		Mn	≤1.25		Si	0.75-1.5		S	≤0.03		P	≤0.03		Cr	24.0-28.0		Ni	32.0-36.0		Nb	0.7-1.6		Ti	0.05-0.25		Pb	≤0.01		Sn	≤0.01		Zr	0.01-0.25		Fe	Balance		Mo	≤0.5		Cu	≤0.25		As	≤0.01		V	≤0.10		Al	≤0.05		W	≤0.30		Zn	≤0.01	
Element	Mini-Max	Remarks																																																																		
C	0.35-0.45																																																																			
Mn	≤1.25																																																																			
Si	0.75-1.5																																																																			
S	≤0.03																																																																			
P	≤0.03																																																																			
Cr	24.0-28.0																																																																			
Ni	32.0-36.0																																																																			
Nb	0.7-1.6																																																																			
Ti	0.05-0.25																																																																			
Pb	≤0.01																																																																			
Sn	≤0.01																																																																			
Zr	0.01-0.25																																																																			
Fe	Balance																																																																			
Mo	≤0.5																																																																			
Cu	≤0.25																																																																			
As	≤0.01																																																																			
V	≤0.10																																																																			
Al	≤0.05																																																																			
W	≤0.30																																																																			
Zn	≤0.01																																																																			
11																																																																				
12																																																																				
13																																																																				
14																																																																				
15																																																																				
16																																																																				
17																																																																				
18																																																																				
19																																																																				
20																																																																				
21																																																																				
22																																																																				
23																																																																				
24																																																																				
25																																																																				
26																																																																				
27																																																																				
28	2. Mechanical Property at Room Temperature Tensile strength : ≥450 MPa Yield strength (Rp 0.2) : ≥ 250 MPa Elongation (4d) : ≥8% for tube, ≥6% for static casting																																																																			
29																																																																				
30																																																																				
31																																																																				
32																																																																				
33																																																																				
34	1.0	02/May/23	REVISED WHERE INDICATED.	E. Formilli	S. Chegini	E. Formilli																																																														
35	0.0	18/Apr/23	FIRST ISSUE	E. Formilli	S. Chegini	E. Formilli																																																														
36	Rev.	Date	Description	Orignated	Checked	Approved																																																														

	ESLAM ABAD GHARB GAS TO METHANOL AND PVM PLANT																																						
Page	MATERIAL DATA SHEET FOR CATALYST TUBES	Rev.	Class																																				
4 of 5	GTP-VD-10-20-ME-DSH-SH504	D0	B																																				
2 of 3	P1003-MEC-MDS-1001	1.0	---																																				
1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26 27 28 29 30 31 32 33 34 35 36	Project No23057 (NH25-35MIC)																																						
3. Mechanical Property at Room Temperature after Aging at 1100°C for 1000hrs																																							
(Typical value) 																																							
Tensile strength : 575 MPa																																							
Yield strength (Rp 0,2): 260 MPa																																							
Elongation (5d): 13%																																							
4. Typical Mechanical Property at High Temperatures 																																							
(80% of typical value as the criteria)																																							
<table border="1" style="width: 100%; border-collapse: collapse; text-align: center;"> <thead> <tr> <th style="width: 25%;">Temperature (°C)</th> <th style="width: 25%;">Ultimate Strength (MPa)</th> <th style="width: 25%;">Yield Strength (MPa)</th> <th style="width: 25%;">Elongation (5d,%)</th> </tr> </thead> <tbody> <tr><td>200</td><td>466</td><td>211</td><td>12.5</td></tr> <tr><td>400</td><td>442</td><td>191</td><td>12.5</td></tr> <tr><td>600</td><td>435</td><td>167</td><td>16.5</td></tr> <tr><td>800</td><td>244</td><td>133</td><td>27.5</td></tr> <tr><td>900</td><td>155</td><td>86</td><td>37.5</td></tr> <tr><td>1000</td><td>101</td><td>59</td><td>50.0</td></tr> <tr><td>1100</td><td>70</td><td>45</td><td>49.5</td></tr> </tbody> </table>				Temperature (°C)	Ultimate Strength (MPa)	Yield Strength (MPa)	Elongation (5d,%)	200	466	211	12.5	400	442	191	12.5	600	435	167	16.5	800	244	133	27.5	900	155	86	37.5	1000	101	59	50.0	1100	70	45	49.5				
Temperature (°C)	Ultimate Strength (MPa)	Yield Strength (MPa)	Elongation (5d,%)																																				
200	466	211	12.5																																				
400	442	191	12.5																																				
600	435	167	16.5																																				
800	244	133	27.5																																				
900	155	86	37.5																																				
1000	101	59	50.0																																				
1100	70	45	49.5																																				
5. Physical Properties 																																							
<table border="1" style="width: 100%; border-collapse: collapse; text-align: center;"> <thead> <tr> <th rowspan="2" style="width: 10%;">Density</th> <th colspan="4" style="width: 40%;">Coefficient of expansion (10⁻⁶/°C)</th> <th colspan="4" style="width: 20%;">Modulus of elasticity (GPa)</th> <th colspan="3" style="width: 30%;">Thermal Conductivity (W/M · k)</th> </tr> <tr> <th style="width: 10%;">Kg/dm³</th> <th style="width: 10%;">20-800°C</th> <th style="width: 10%;">~900°C</th> <th style="width: 10%;">~1000°C</th> <th style="width: 10%;">~1100°C</th> <th style="width: 10%;">800°C</th> <th style="width: 10%;">900°C</th> <th style="width: 10%;">1000°C</th> <th style="width: 10%;">1100°C</th> <th style="width: 10%;">800°C</th> <th style="width: 10%;">1000°C</th> <th style="width: 10%;">1100°C</th> </tr> </thead> <tbody> <tr> <td>8.03</td> <td>17.3</td> <td>17.8</td> <td>18.6</td> <td>19.1</td> <td>115</td> <td>112</td> <td>108</td> <td>102</td> <td>23.5</td> <td>27.8</td> <td>29.5</td> </tr> </tbody> </table>				Density	Coefficient of expansion (10 ⁻⁶ /°C)				Modulus of elasticity (GPa)				Thermal Conductivity (W/M · k)			Kg/dm ³	20-800°C	~900°C	~1000°C	~1100°C	800°C	900°C	1000°C	1100°C	800°C	1000°C	1100°C	8.03	17.3	17.8	18.6	19.1	115	112	108	102	23.5	27.8	29.5
Density	Coefficient of expansion (10 ⁻⁶ /°C)				Modulus of elasticity (GPa)				Thermal Conductivity (W/M · k)																														
	Kg/dm ³	20-800°C	~900°C	~1000°C	~1100°C	800°C	900°C	1000°C	1100°C	800°C	1000°C	1100°C																											
8.03	17.3	17.8	18.6	19.1	115	112	108	102	23.5	27.8	29.5																												

Project No23057 (NH25-35MIC)

6. Larson Miller Curve (Stress Rupture Strength) Δ



7. Stress Rupture Strength Table Δ

Temperature (°C)	1000hours Rupture Stress		10000hours Rupture Stress		100000hours Rupture Stress	
	Average (MPa)	Minimum (MPa)	Average (MPa)	Minimum (MPa)	Average (MPa)	Minimum (MPa)
850	62.5	61.2	50.6	49.3	40.1	38.8
900	48.8	47.6	38.1	36.8	28.9	27.6
950	37.0	35.8	27.6	26.4	19.9	18.6
1000	27.1	25.8	19.2	17.9	13.0	11.7
1050	19.0	17.7	12.7	11.4	8.3	7.0
1100	12.8	11.5	8.2	6.9	5.2	4.1
1125	10.3	9.1	6.4	5.3	4.2	3.2

NOTE: Calculate allowable stress for static casting as 90% of Larson Miller Curve shown

Edited: Lu Congcong 陆丛丛

Checked: Rinkal Dogra

Approved: Wang Zhenhua 王振华

