

START

START CERA-TECH CO., LIMITED

Add: Room 13, 27/F, Ho King Commercial Centre, 2-16 Fa Yuen Street,
Mongkok, Kowloon, Hongkong, China

Tel: 0086-18666376186 Email: tom@start-ceratech.com

Technical Data

- (1). Name: PSD-308D Scanning ceramic tile detection machine.
- (2). Technical data: Power distribution three-phase AC 380V, single-phase AC 220V;
Power 2.2KW, power air source 4-6kg.
- (3). Machine Size: 4200X1750X1550 (L*W*H)
- (4). Range of application: 600X600mm, 400X1200mm, 600X1200mm, 800X800mm,
1000X1000mm, 1200X1200mm;
- (5). Equipment detection accuracy: $\leq 0.10\text{mm}$.
- (6). Speed: 600X600mm $\leq 60\text{pcs/min}$;
400X1200mm $\leq 35\text{pcs/min}$;
800X800mm $\leq 50\text{pcs/min}$.



START CERA-TECH CO., LIMITED**Add: Room 13, 27/F, Ho King Commercial Centre, 2-16 Fa Yuen Street,
Mongkok, Kowloon, Hongkong, China****Tel: 0086-18666376186 Email: tom@start-ceratech.com****START**

PSD-308D spare parts list:				
NO.	Name	Model	Brand	QT'Y
	Hardware frame	PSD-308D	Passed	1set
	Platform glass	customization	Passed	1pc
	Transmission belt	customization	HAOTUO	1pc
	Frame surface treatment	Electroplate	-----	1set
	Pneumatic parts	multiple	AirTAC	1set
	Motor reducer	RK64-2.2 KW	LUODE	1set
	Driving Bearing	several	----	1set
	PLC	AFPOHC32ET	Panasonic	1set
	Mainbord	STM32PLC.PCB	Passed	1set
	Singlechip	PSD-308 host	Passed	1set
	Invertor	V20	Siemens	1set
	Display	17.3 inch	Passed	1set
	Laser sensor	IL-S065	Keyence	6sets
	Grating Encoder	K6015D2-5000BM-K830	ROTARY ENCODER	1set
	Electri items	-----	-----	1set
	Computer	-----	-----	1set
	Camera	MV-CA013-AOGM	CONWY	4sets
	FA Lens	25mmF/2.8	CONWY	4sets
	Sliding block	LSH20HN	Air TAC	4sets
	Servo motor	SV-X2MH040A	Hechuan	3sets