

Full automatic high speed pressure Strapping Machine



— The design ,planning and manufacturing of packing scheme
青岛艾讯包装设备有限公司
 QINGDAO AUSENSE PACKING EQUIPMENT CO.,LTD



To	/	From	Qingdao Ausense Packing Equipment Co.,Ltd		
Attn	/	Attn	Ms Nancy Wang		
Tel	/	Tel	0086-17863931924		
Fax	/	Fax	0086-532-81731822		
Email	/	Email	seller-04@yupack.com		
Skype	/	Skype	+867863931924		
Website	/	Website	www.yupack.com		
Quote	Date	10/17/2023	Valid	30days	Warranty 12months



Automatic high-table pressurized strapping machine is a automatic pressure for loose items packaging operations, the up and down movement of the machine by the cylinder to realize the compression of the item at the same time of compression will be automatic strapping machine, thus will decrease the volume of goods, so as to reduce the cost during the transit. The machine has high-table and low-table models.

Machine description:

- 1.Full automatic machine, working with sensor test the proucts, PLC control system
- 2.Unique design tension, tightening stronger
- 3..Clam shell panels, repair warranty, easy to maintenance
- 4.The new electric devices, heating fast, long life
- 5.Single-chip electronic control, fully functional, easy to operate
- 6.Pressure set according to requirements,firm structure, easy to operate.
- 7.Be in accordance with the need to select pneumatic or hydraulic cylinders, pressurized product be solid and firm, save space and freight.
- 8.Suitable for canvas, cement bag, all kinds of bulk goods bale.
- 9.According to customer demand, customized compression packer, includes the choice of the design of the cylinder pressure, cylinder, the platform width, the size of the gantry As well as the bearing mesa design, etc

Technological parameters:

Model	YS-LX309
Strapping speed	Max 2.5 second/strap
Frame size	W1450mm*H600mm
Top pressure traveling	0-400mm
Working table height	850mm
Roller Diameter	50mm, Pitch:80mm
Strap width	9mm
Voltage	380V 50Hz 3p
Power	0.75KW
Net weight	260kg

Machine parts picture**Standard machine detail picture:**







