Rotary Vane Vacuum Pumps SD Series

# 2015SD 2021SD PASCAL Series PASCAL Series



2005SD CFM 3.8 2010SD CFM 6.8 2015SD CFM 10.6 2121SD CFM 14.6

Alcatel Adixen Pascal Series 2005SD - 2010SD - 2015SD - 2021SD

2 Stage Rotary Vane Vacuum Pump

## From 3.8 to 14.6 CFM

- compact design : reduced dimensions, choice of horizontal or vertical inlet and exhaust ports, all controls and service access located on the front.
- optimized tightness : integrated anti-suckback; all static sealings secured by O-rings; external shaft seal can be renewed easily, without dismantling the pump.
- high pumping speed from atmosphere to vacuum.
- · efficient gas ballast for vapor pumping.
- · air cooled for optimum performance
- field serviceable using the appropriate maintenance kits



SD Series rotary vane pumps address the requirements of all major vacuum applications in diverse industries.

#### SD 2005-21 PASCAL Series 2 Stages


Specifications		Units	2005SD	2010SD	<b>2015SD</b>	<b>2021SD</b>
Part Number			P102308	P102309	P102310	P102311
New Pump Price (2008 List Prices)			\$2,080.00	\$2,340.00	\$2,760.00	\$3,190.00
Nominal pumping speed	50Hz	m³/h	5.4	9.7	15	20.7
	60Hz	cfm	3.8	6.8	10.6	14.6
Pneurop pumping speed	50Hz	m³/h	4.8	8.5	12	15.5
	60Hz	cfm	3.4	6	8.8	11.8
Ultimate partial pressure		mbar	10-4	10-4	10-4	10-4
Ultimate total pressure closed gas ballast		mbar	2.10 -3	2.10 -3	2.10 -3	2.10 -3
Ultimate total pressure open gas ballast		mbar	10-2	10-2	10-2	10-2
Water vapor capacity	50/60Hz	g/h	120/110	125/100	110/100	90/90
Water vapor pressure	50/60Hz	mbar	35/25	20/15	12/10	7/7
Weight (max)		kg (lbs)	25 (55)	26 (57.2)	27 (59.4)	28 (61.6)
Pump Dimensions		BackPage	BackPage	BackPage	BackPage	BackPage
		3 phase 342V to 460V 50hz, 342V to 520V 60hz, 170V to 254V 50hz, 170V to 300V 60hz 1 phase 180V to 254V 50/60hz, 90V to 132V 50/60hz				
Max nominal power rating 50/60Hz		kW	0.45/0.55	0.45/0.55	0.45/0.55	0.45/0.55
Min ambient temperature		°C (°F)	12 (54)	12 (54)	12 (54)	12 (54)
Max ambient temperature		°C (°F)	45 (113)	45 (113)	45 (113)	45 (113)
Oil capacity		I	0.83	0.95	0.95	0.98
Inlet flange		ISO-KF	DN 25	DN 25	DN 25	DN 25
Exhaust flange		ISO-KF	DN 25	DN 25	DN 25	DN 25



To Our Website idealvac.com

Ideal Vacuum Products, LLC 2401B Phoenix Ave. NE Albuquerque, NM 87107 Phone: (505) 872-0037 idealvac.com or pchemlabs.com

#### Dimensions for SD Series Vacuum Pumps



Specific Dimensions in mm				
SD Series	L mm			
2005SD	228			
2010SD	245			
2015SD	270			
2021SD	291			
*same dimensions for single				
and three-phase motors				

### Accessories for SD Series vacuum pumps



#### Oil Mist Exhaust Filters KF/NW25

Oil Mist Exhaust Filters retain oil mist contained in the exhausted gases with a high level of separation.



Up to 10 CFM for 2005, 2010SD P/N P102027 \$143.00 Replacement Cartridge P/N GL915 \$27.00



Up to 16 CFM 005-2021SD P/N P102028 \$226.00 Replacement Cartridge P/N FG9 \$30.60



idealvac.com

Up to 20 CFM P/N P102029 \$315.00 Replacement Cartridge P/N EEPS6925 \$54.00



Up to 24 CFM P/N P101878 \$165.00 Replacement Cartridge P/N P101882 \$44.00

(All Filters come With Media)

# Alcatel, Adixen, Oil Mist Eliminators (OME)

Oil Mist Eliminators retain oil mist contained in the exhausted gases with a high level of separation; an internal over pressure valve prevents exceeding



vacuum products

(505) 872-0037

#### Alcatel, Adixen, Inlet Dust Filter

Inlet Dust Filters will prevent solid particles from entering into the rotary vane pump and avoid concentration of solid media which can act as an abrasive and shorten the pump life.



2401B Phoenix Ave. NE Albuquerque, NM 87107 Phone: (505) 872-0037 idealvac.com or pchemlabs.com

Rev. 1mar 2009