

ZONI CARLO 8

Viale Euro 26020 – Acquanegra G Select Language v ITAL\





A self propelled machine on 4 driving wheels with hydrostatic traction provided by engines "Poclain" on wheels.

The variable carriageway permits the shifting of the wheels up to 100 cm simply acting on a lever.

It can be equipped with different types of detasseling bars: cut by knives, pull through discs or rollers. All bars are 3 + 3 or 4 + 4 and allow the mounting of the photocells (electronic eye) for automatic processing.

ENGINE	DEUTZ TD2011L04 57.6 kW or DEUTZ TD 2.9 55.4 kW
TRACTION	Fully hydrostatic on 4 driving wheels with radial piston hydraulic motors and Twin Lock system.
CARRIAGEWAY	Hydraulic variable from a minimum of 200 cm to a maximum of 310 cm.
STEERING	2 steering wheels (front) with hydrostatic system and power steering
HYDRAULIC OIL TANK	140 litres
SUSPENSIONS	Pneumatic
FRAME STRUCTURE	200 x 200 mm, square tubular 200×100 mm or 100 x 100 mm.
GROUND CLEARANCE	170 cm.
TYRES DIMENSION	Measure 11.2-24 TT High Traction
STARTER	Electric with battery 12 V
PULLING BAR	Equipped with rollers for 6 or 8 rows (3 + 3 or 4 + 4)
CUTTING BAR	Equipped with knives for 6 or 8 rows (3 + 3 or 4 + 4)
WATER TANK	1000 liters
SPRAYING BAR	Fully hydraulic opening / closing and lifting / lowering system, 12, or 15 meters length with noozles TREJET and descents for the distribution of the product
ACCESSORIES	Photocells for automatic castration work









