

350 Vacuum homogeneous emulsifier

product	Material specifications	Origin name
Pot body	Inner layer 316 stainless steel 5mm, middle layer 4mm, outer bladder 304 stainless steel 3mm	TISCO (Taiyuan)
	Means layer 304L stainless steel 3mm	
body frame	Q235, surface paint coated stainless steel	Wuxi
Digital display temperature sensor	Probe penetration type temperature measurement	
Sanitary valve	Health level	Wande (Wuxi)

hydraulic pressure station	Pump flow rate 14 L/min, fuel tank 40L, motor power 2.2kw	Wuxi
Stir system	Mixing the deceleration motor;	Qi Peng (Wuxi)
	Mixing box (mixing shaft, stainless steel blade) frame scraping wall two-way mixing	304 Stainless steel
Vacuum pump (sheet selection type)	Motor: 3kw 380V	Nanguang (Zhejiang)
	check valve	
Hydraulic lifting system	Motor: 2.2kw 380V cylinder	(Wuxi)
Homogenous motor	7.5KW	Siemens, (Bed)
Stir the motor	4KW	Creative benefit (Changzhou)
frequency transformer	VD100	Watson (Hunan)

electrical equipment	AC contactor, intermediate relays, air switch	Drlicey, Schneider
bearing	SKF/ Harbin	(Sweden), Harbin
grease seal	Fluorine rubber inner skeleton lip ring	Taiwan
gear wheel	Quality control occupation of fire tooth surface hardening treatment precision grinding processing	process
grease	Semi-flow grease,, high-speed bearing special fat	Kunlun card

Provide sealing ring, one frame oil seal and one kit