

## 100533055-The Catalog of Check valve and Nozzle

### ITEM 1- Check Valve



#### **(B)10742A**

Made in choice of brass or aluminum.  
Check valve opens at 7 PSI (0.5 bar) pressure.  
1/4" NPT (M) inlet and (F) outlet connections.  
Overall length 1 7/16" (37 mm). Flow rate of  
2.25 GPM at 5 PSI pressure drop (8.5 l/min at  
0.34 bar). Weights: brass 2 1/2 ounces (71 g),  
aluminum 2 ounces (57 g).

(B)=BSPT

### ITEM 2- Nozzle Body

#### TeeJet Nozzle Bodies



**Type-TT**  
Male Inlet NPT  
or BSPT Connection

TEEJET BODY NUMBER	FOR TEEJET NOZZLE TYPE	MALE SIZE	MATERIAL
CP(B)1336	1/8TT	1/8"	Brass
CP(B)1322	1/4TT	1/4"	Brass
CP(B)8028-NYB	1/4TT-NYB	1/4"	Nylon
CP(B)1322-I	1/4TT-I	1/4"	Steel
CP(B)1322-SS	1/4TT-SS	1/4"	Stainless Steel
CP(B)1324	3/8TT	3/8"	Brass
CP(B)1340	1/2TT	1/2"	Brass
CP(B)3818	3/4TT	3/4"	Brass
CP(B)3818-SS	3/4TT	3/4"	Stainless Steel

(B) = BSPT

## ITEM 3- Nozzle Cap

CP1325



CP18032A-NYB



### TeeJet Nozzle Caps

Secure interchangeable TeeJet tips to the various nozzle bodies. 18032A-NYB winged TeeJet cap allows quick change of spray tips with no tool required.

TEEJET CAP NUMBER	DESCRIPTION
CP1325	Brass
CP8027-NYB	Nylon
CP8027-1-NYB	Nylon (Extra-long size)
CP1325-AL	Aluminum
CP1325-SS	Stainless Steel
CP18032A-NYB	Winged Cap, Nylon
CP3819	Brass, use with 3/4T & 3/4TT body
CP3819-SS	Stainless Steel, use with 3/4T & 3/4TT body
CP20230	Brass, use with ceramic disc-cores