

# QUOTATION



Name: Rin Chow  
Position: Sales Engineer  
Website: [www.lanson-imm.com](http://www.lanson-imm.com)  
Tel: +86-757-29965888  
Mob: +86-13450475653  
Factory Address: Shunde Town Foshan  
City Guangdong Province China

# Company Profile



Founded in 2005, Lanson Precision Machinery Co., Ltd is a national high-tech enterprise, covers an area of 100 thousand square meters, locating in the heavy industry city - Shunde, Foshan City.

Lanson has advanced equipment for designing processing, manufacturing and testing. Our major products are plastic injection moulding machines and die casting machines for aluminum and magnesium. We dedicate to provide professional turn-key moulding solution to customers.



Name: Rin Chow

Position: Sales Engineer

Website: [www.lanson-imm.com](http://www.lanson-imm.com)

Tel: +86-757-29965888

Mob: +86-13450475653

Factory Address: Shunde Town Foshan City Guangdong  
Province China

## Quotation

To:	ABDOLAZIM AKBARI	From:	Lanson Precision Machinery Co., Ltd
Address	Bandar Abbas, iran	Address	528300 Shunde Foshan City Guangdong Province
Validity	Till to 2023-4-30	Company license no.	91440606771895746M
Date:	<a href="#">2023/3/2</a>	Email	<a href="mailto:rin@lanson-imm.com">rin@lanson-imm.com</a>
Quotation NO.	<a href="#">LS230302IMM</a>	Tel:	<a href="tel:008613450475653">008613450475653</a>

Energy Saving servo system IMM			Currency: Abroad RMB Payment (FOB Shenzhen China) Noted: HK belongs to China. RMB can not sent from HK only accept paid from abroad RMB account.	
Model	FOB Nansha Unit Price (RMB)	QTY	FOB total amount (RMB)	Notes
GT-LS800S (D100mm)	¥966,000	1	¥966,000	380V/3PH/50HZ
GT-LS1400S (D100mm)	¥1,656,000	1	¥1,656,000	
GT-LS1800S (D100mm)	¥2,173,500	1	¥2,173,500	
Estimated CFR cost for 800S	¥82,800	1	¥82,800	40HQ *2
Estimated CFR cost for 1400S	¥207,000	1	¥207,000	20GP*2 20FR*1 40GP*1 40FR*1
Estimated CFR cost for 1800S	¥276,000	1	¥276,000	20FR*2 40GP*1 40HQ*2 40FR*1
<b>Total</b>			<b>¥5,361,300</b>	

**Price Validity: 30 days**

1/ Trade Term: FOB Nansha RMB/PC

2/ Payment term: T/T 40% deposit prepayment and balanced paid before shipment. RMB can not sent from HK only accept paid from abroad RMB account.

3/ Packaging: Standard ocean freight packing

4/ Port of loading: Nansha port in Guangdong Province, China

5/ Destination: TBC

6/ Shipping mark: Lanson

7/ Delivery: in 180 working days after seller received 40% deposit and signed PI

8/ Country of Origin: China

9/ Bank information:

Beneficiary name: Lanson Precision Machinery Co.,Ltd.

Beneficiary bank: GUANGDONG SHUNDE RURAL COMMERCIAL BANK COMPANY LIMITED

Address: 38 Feng Shan Zhong Road, Daliang, Shunde, Guangdong 528300, P.R.C

Swift code: RCCSCNBS

Account No.: 01618000002316

**Warranty Policy**

1/ Warrantee period for major component parts, fixed platen, moving platen, tail platen and tie bars, are 18 months. Other components are 12 months;

2/ Easily broken parts such as screw, screw tip set and heater bands are not covered by this warranty. We strongly suggest local agent to keep stock of these parts in order to facilitate after sales service;

3/ Use of courier express is subject to spare parts under warranty period which is weight less than 5kgs. For those parts weight more than 5kgs will use alternative delivery method such as cargo shipment or further negotiation between end users and Lanson.

**Price listed above is including the following features:**

- 1 380V /3ph / 50hz
- 2 Injection unit with Linear guide way, low friction during injection
- 3 Two set of hydraulic core pulling device
- 4 Four set of air blast device
- 5 Ceramic heaters
- 6 Window for monitoring screw rotation
- 7 Double layer barrel cover
- 8 Embedded mechanical safety lock
- 9 Reinforced toggle – Stronger, longer service life
- 10 Oil tank cover with drain, easy oil tank cleaning access and more convenience
- 11 Check valve in Oil lubrication bypass filter –Prevent dirty oil from sucking back
- 12 Socket and wire protection connection
- 13 Protection cover for Linear transducers
- 14 Nozzle cover with window and sensor
- 15 Low pressure mold protection
- 16 Automatic mold height adjustment
- 17 Automatic clamping force adjustment
- 18 Techmation controller system
- 19 Linear transducer for injection, clamping and ejector
- 20 RPM display
- 21 Level pad
- 22 Three color alarm light
- 23 Standard spare parts
- 24 Energy saving servo system
- 25 T slot with tap holes



Model	Unit	GT-LS800S			GT-LS1400S			GT-LS1800S						
International size rating		8000-5755			14000-14339									
INJECTION UNIT														
Screw size		A	B	C	A	B	C	A	B	C	A	B	C	
Screw Diameter	mm	90	100	105	120	130	140	130	140	150	140	150	165	
Theoretical shot volume	cc	3181	3927	4330	7125	8362	9698	8893	10314	11840	11161	12812	15502	
Theoretical shot weight (PS)	g	2894	3573	3939	6483.9	7609.5	8825.3	8093	9386	10774	10156	11659	14107	
Screw L:D ratio	L/D	24.4	22	21	22.8	21	19.5	22.6	21	19.6	22.5	21	19.1	
Injection pressure	Mpa	181	147	133	201	171	148	171	148	129	180	157	130	
Screw speed	rpm	120			95			100						
Plasticizing capacity (PS)	g/s	96.9	131.6	131.9	173	203	235.4	215.7	250.1	287.1	200.1	229.7	278	
CLAMPING UNIT														
Clamping force	KN	8000			14000			18000						
Mold opening stroke	mm	1025			15000			1650						
Space between tie bar	mm	1000*1000			1450*1350			1660*1550						
Mold thickness min	mm	380			650			750						
Mold thickness max	mm	975			1400			1600						
Ejector force	KN	289			303			430						
Ejector stroke	mm	300			380			400						
Number of ejectors	pcs	25			29			29						
OTHERS														
Pump motor	KW	90			135			135			156			
Hydraulic system pressure	Mpa	17.5			17.5			17.5						
Heating capacity	KW	43			74			89			100			
Oil tank capacity	L	12000			2000			2100						

# COMPANY CULTURE



1) Responsibility is the embodiment of goals and missions of an enterprise, and is also intrinsic motivation of working passion of the staff.

2) Professionalism is basic requirement of staff in Lanson. Attentiveness is our impetus of continuous improvement.

3) Team is leading guarantee of comprehensive competitive power with resource integration and increase of efficiency under of enterprise mission.



Name: Rin Chow

Position: Sales Engineer

Website: [www.lanson-imm.com](http://www.lanson-imm.com)

Tel: +86-757-29965888

Mob: +86-13450475653

مشخصات فنی همانطور که در فایل پیوست آمده به شرح زیر است :

دستگاه تزریق پلاستیک تعداد ۳ دستگاه

کاربرد : تولید قطعات پلاستیکی بنده تریلی و کامیون

۱- دستگاه تزریق پلاستیک GT-LA۰۰S

وزن دستگاه : ۵۶ تن

۲- دستگاه تزریق پلاستیک GT-LS ۱۴۰۰S

وزن دستگاه : ۶۵ تن

۳- دستگاه تزریق پلاستیک GT-LS ۱۸۰۰S

وزن دستگاه : ۷۵ تن

بقیه مشخصات فنی طبق پروفورما بالا می باشد