

The problems ...did you know?

If Strapping 60 pallets per day with 4 straps each pallet

That means the operators at least per year:

- 120,000 x times bending down
- 60,000 x times raising straps
- 60,000 x times carrying the strapping tool



Bending down



Raising straps



Carrying tool by hand

Our solution



Standing



Strap right into the hand



Carrying by tool-lift

Ergonomic

Roll the JD-008 in position. The chainlance pulls the strap through under the pallet and up again on the rear side and over the pallet...

Easy

...straps is right into the hand of the operator. Then the ChainLance retracts. The strap lifter hands the other end of the strap to the operator at working height...

Efficient

...and the strap is tensioned and welded in seconds by the sealing head.

...with JD-008

If Strapping 60 pallets per day with 4 straps each pallet

That means for the operators exactly per year:

- 0 x times bending down
- 0 x times raising straps
- 0 x times carrying the strapping tool



The Ergonomic Pallet Strapping Machine for PP/PET strapping



Advantage



- *Elegant operation via touchscreen and joystick
- *Easy going & comfortable handling with ergonomically shaped handles
- *Fully covered for increased working safety in classy design
- *Auto strapping, feeding and sealing
- *3 times higher efficiency
- *The pallet width is adjusted not mechanically by touch screen
- *Applicable for object : Width below 2000mm, height below 3000mm
- *Number of strapping: 400 to 600 per charge

Structure



Characteristics

| | |
|------------------------|---|
| Dimensions: | 950mm*750mm*1250mm |
| Net weight: | 105KG-110KG; |
| Chain lance length: | 9300mm |
| Drive: | Electric motor with spur gear, electronically controlled |
| Noise emission level: | 79 dB (A) |
| Max. chain thrust: | 320 N |
| Strap Types: | Polypropylene (PP) /Polyester (PET) |
| Strap thickness: | 0.6mm-1.3mm |
| Strap width: | 12mm-19mm |
| Applicable for object: | Width below 2000mm, height below 3000mm |
| Pallet hole height: | Over 75mm |
| Sealing head: | Optional |
| Charger: | Three stage full intelligent charger |
| Battery: | 33.6V Lithium battery |
| Number of strapping: | 400 to 600 per charge, depending on pallet size tension, friction sealing time and age of battery |

Battery life span: Up to 2000 charges
Charging time: Approx 3.5 hours

Applications

JD-008 is widely used in all industries and sectors

