



SUNKING INTERNATIONAL TRADING(SHANGAHI)CO.,LTD  
ROOM838,NO.1877,CAOAN ROAD,JIADING DISTRICT,SHANGHAI,CHINA

TEL:0086 21 33518045

FAX:0086 21 33518047

SK 288 COVERING MACHINE

288 spindles 12 sections

1. Model: Single package of 12 sections 188 spindles
- 2 spindle: optional straight spindle spindle (Wuxi Hongda Special Parts Factory)
3. Spindle speed: 15000 rpm can be selected according to the limit speed
4. Control system: electronic molding system
5. Rack: optional Mannigatu rack
7. Drafting: single drafting roller. The head has a pressure roller 0.8kg
8. Motor: 5.5KW/7.5KW can be selected
9. Spindle arrangement: optional straight arrangement or arc arrangement
- 10.. 2.0 for moving flower opening
12. The outer retaining rod can be thickened stainless steel tube or purchased locally, which can be installed more firmly.
13. Forming paper tube length: 225m



型式	
锭子型式 Spindle type	双面双层 Two sides and two layer
收卷型式 Take up type	双面双层 Two sides and two layer
整机尺寸 Overall dimension (L*W*H)	24244.8 x 1400 x2176
单节长度 each section length	1830
节数 Section no.	12
锭子 Spindle	
锭位 Spindle no.	288
每节锭位 Each section spindle no.	24
锭距 Spindle gauge	270
锭速 Spindle speed (max)	15000
捻向 direction	S/Z
捻度 Twist no.	200-2500
铝管尺寸 Aluminum Bobbin Size	30X36X84X140
收卷拉比 Take up Draft	
收卷形式 Take up forming mode	电子成型 electronic traverse
收卷管尺寸 Take up Bobbin size	L 220 xØ68x Ø72
单包收卷个数 Position of single covering	288
双包收卷个数 Position of double covering	144
收卷重 take up bobbin weight	2000
拉比 Draft	1.4-3.8 (if 1.4-2 .2 need modi
电机 Power	
主电机 Main motor (2 motor	5.5+7.5
卷绕横动伺服电机 winding motor (1	1.5
电压 Voltage	380 V 3 PHASE 50HZ