

## XH160 型自动装盒机主要技术参数:

### XH160 Automatic packing machine main interface:

电源 Power supply	AC220 volt two-phase three-line system power supply 50Hz Total power 1 kw
Dimension (LxWxH) MM	3600x1350x1750
整机重量 (千克) Wight	1200
生产能力 Capacity	主机运行速度 20--50 盒/分钟 Host running speed is 20- -50 boxes / min
耗气量 Air consumption	20 立方米/小时 (压力 0.5-0.7 兆帕) 20 m <sup>3</sup> /H (pressure 0.5-0.7 mpa)
包装材料 Packing material	纸盒质量: 300-400 克/平方米 (视纸盒尺寸而定) Box Quality: 300-400 g/m <sup>2</sup> (depending on the size of the carton) 规格: 最大尺寸 (长x宽x高) 200*165*60 毫米 Specification: Maximum size (length, width and height) 20016560 mm 最小尺寸 (长x宽x高) 80x60x15 毫米 Minimum size (length, width and height) 80*60*15 mm
说明书 Instructions	Without
压缩空气 compressed air	0.5mpa Flow greater than 0.6m <sup>3</sup> / min

## Main parts list

Name	Qty	Model	Remark	Brand
人机界面 Man-machine interface	1	TK6071IP	威伦 Weinview	台湾 TW
PLC	1	FX3G-40M	可编程控制器 Programmable Controllers	三菱 Mitsubishi
变频器 Inverter	1	FR-D720S-0.75K-CHT	0.75	
接触器 Contactor		LC1-D1810		施耐德 Schneider
断路器 circuit breaker	2	1C3		
	2	2C10		
	1	3C16		
光电开关 Photoelectric switch	1SET	E3V-DS8		欧姆龙 OMRON
继电器 Relay	2	MY4		
继电器组 Relay group	3	G6B-4BD		
开关电源 power supply switch	1	S8X-5024	台湾 TW	明伟 Meanwell
电磁阀 solenoid valve	5	4SV210-08		亚德客 AirTac
调压阀 Pressure regulating valve	1	GFR30008-F1/PT	二联件 Two parts	
真空发生器 vacuum generator		VTM20-C	韩国 Korea	艾康 AiKang
主减速电机 Main deceleration	1	MTD57-Y0.75-4P	380V	恒齿 HENGCHI

motor				
轴承 Bearing	full set	各种规格 All kinds of specifications		哈尔滨 Harbin
耐磨部件 Wear-resistant parts	full set	GCr15		上海宝钢 Shanghai baosteel
不锈钢外罩 Stainless steel cover		SUS304		韩国浦项 South Korea's puxiang
变压器 Voltage transformer				国产 Domestic