

Poz/Pos	Kod/Art. No	Açıklama/Description	HS Code	Adet/Qty	Birim/Unit	B.Fiyat/U.Price	Tutar/Amount
2-1	BT600A-S01	HEAT SEALER		1	PC		
		<p>Compact frame</p> <p>3 (three) axis servo drive</p> <p>Robust frame design with enhanced level ensuring designs.</p> <p>Automatic lubrication for servo drives</p> <p>All position parameters by recipe based changeover</p> <p>Double side seal squeezing system</p> <p>Separate timing availability for melting of lid and cover</p> <p>Correct lid pick detection system</p> <p>Fast and easy lid holder fitting</p> <p>Self setting lid holder design</p> <p>Lid pick control</p> <p>Precision and rugged heat platen linear guiding</p> <p>Slow rising availability – reducing plastic sticking</p> <p>Torque based sealing finish availability</p> <p>Container lifting with precision datum setting</p> <p>PLC based temperature control</p> <p>SSR based heater activation for precise PID control</p> <p>Current control for all platen heaters</p> <p>Multi zone platen temperature control</p> <p>Stainless steel main heating platen</p> <p>Special alloy mirrors</p> <p>Alternate mirrors preheating and quick changeover</p> <p>Fume collection facility and hood</p> <p>Moveable preheat guards</p> <p>Self setting lid holder design</p> <p>Spring loaded battery stopper</p> <p>Battery stopper setting by dedicated jigs</p> <p>Recipe based changeover</p> <p>1x6 and 2x3 cell battery range processing</p> <p>Chain drive battery conveyor</p> <p>Entry section stop / go device</p> <p>Inox battery guides</p> <p>Safety fences at the rear side of the machine.</p> <p>Touch screen HMI - Siemens</p> <p>Polycarbonated doors and guarding at the front side of the machine</p> <p>Aquistic and visual alarm</p> <p>Pressure control for compressed air supply</p> <p>Lock type pressure regulators</p> <p>Safety stopper for overhead vertical drives</p> <p>Standalone switchboard cabinet</p> <p>Padlock type main switch</p> <p>English operator buttons</p> <p>English HMI menu</p> <p>CE compliant</p> <p>Standard machine colour in RAL5023 Distant Blue and RAL7035 Light Grey</p> <p>Includes one set of tooling</p> <p>3,0 batts/min (DIN44) battery processing</p> <p>PLC : Siemens S7</p> <p>HMI : Siemens</p> <p>Gearmotors : SEW</p> <p>Servo Motors : SEW</p> <p>Pneumatic : FESTO / SMC</p> <p>Power : 220/380V – 3 Ph – 50 Hz</p> <p>Installed Power : 42 Kw (Standard version)</p> <p>Compressed Air : 6 Bar – 1m3/h</p> <p>Noise Level : ≤85 dB</p>					



