

BIRD
UV

UV LED Curing System for Label Flexo Press



BIRD
UV

SPECIFICATIONS

COB Based	Copper
POWER	30 Watt/cm ²
Wiring Type	Gold
LED Brand	SEOUL SEMICONDUCTOR COMPANY Ltd. High Power UV LED
UV LED Width	260 to 1040 mm Width UV LED Cassette Available.
Printing Speed	120-150 Meters / Minute Depending on the raw material used
Lens	Focus Lens for high intensity
Chip Size	52mmX22mm
Cooling Process	Water Cooled
Substrate	High Quality Copper
Main Application	UV LED Ink Drying for Offset Press
Wavelength	395nm
Product Life	20,000 Hours service life.
Power Protection	Surge voltage protection, short-circuit protection, earth leakage protection,
LED Secondary optical Design	High purity quartz and excellent optical design are used to make secondary optical lens, which makes the LED UV energy density high temperature, ensure curing effect and reduce material temperature at the same time.
Characteristic	<ol style="list-style-type: none">1. Best quality COB package, special structure design good heat dissipation, very strong light intensity max 30W/cm²2. One color corresponding one UV LED driver and one UV LED lamp, Easy to control and after service3. Light intensity change will according printing speed4. Cool light, Aluminum foil, film is also suitable for printing, such as PVC, PE, PET.

+86- 13725544782

 www.birduv.com

 michael@birduv.com

Company: Shenzhen Bird UV Technology Co., Ltd
Address: 801, Block B-14, the First industrial of BAIHUA Community, Guangming street
, Guangming, Shenzhen, Guangdong, 518107, China