

با سلام

ویژگی ها و قابلیت هایی ممتاز دستگاه در مشابه با ساخت داخل:

۱- قابلیت نصب فیلترهای هوایی جهت ماشینکاری قطعات گرافیت.

۲- محیط بسته کاور دستگاه

۳- اسپیندل ۱۰،۰۰۰ دور بر دقیقه

۴- کنترل فانوک

۵- دستگاه با محورهای لینیر و سرعت ماشینکاری تا ۲۳ متر بر دقیقه

standard features

- 10.4" Color LCD
(8.4" on GX 300, 480, 510 & 710)
- AI Contour Control
(option on GX 480 & GX 710)
- Manual Guide i (manual guide Oi
on GX 480 & GX 710)
- Max Controlled axes 5
- Simultaneous controlled axes 4
- DNC operation with memory card
- Program restart
- Dry run
- Fine Acc & Dec control
- Least input increment
- 0.001mm, 0.001deg.
- Servo control HRV3
- Backlash compensation
- Linear interpolation
- Chamfering and corner rounding
- Coordinate system rotation
- Scaling
- Cylindrical interpolation
- Helical interpolation
(Circular interpolation plus Max. 2
axes linear interpolation)
- Polar coordinate command
- Circular interpolation
(Multi-quadrant is possible)
- Programmable mirror image
- Background editing
- Extended editing
- Dynamic graphic display
- Nano interpolation
- Rigid tapping
- Multi language display
- Run hour and parts count display
- Automatic acceleration /deceleration
- Automatic corner override

- Rapid traverse: linear Cutting feed:
exponential
- Tool offset pairs, ± 6 digits, 400 pairs
- Tool length compensation
- Tool offset memory C
- Part program storage length 1280 m
- Number of registered programs 400
- Self-diagnosis function
- Alarm history display
- Operation history display
- Help function
- Stored pitch error compensation
- Sub call
- Custom Macro B
- Additional custom macro variables
- Canned cycles for drilling
- Small hole peck cycle
- Tool life management
- Workpiece coordinate system,
G52 - G59
- Addition of workpiece coordinate
system 48 pairs
- Automatic tool length measurement
- Inch / Metric
- Embedded Ethernet









High Speed Grinding Sp...

\$200.00

AD • 0.0 ★ \$200.00

source now

CONTRO



STANDARD FEATURES

- 10.4" Color LCD (8.4" on GX 300, 480, 510 & 710)
- AI Contour Control (option on GX 480 & GX 710)
- Manual Guide I (manual guide On on GX 480 & GX 710)
- Max Controlled axes 5
- Simultaneous controlled axes 4
- DNC operation with memory card
- Program restart
- Dry run
- Fine Acc & Dec control
- Least input increment - 0.001mm, 0.001deg.
- Servo control HRV3
- Backlash compensation
- Linear interpolation
- Chamfering and corner rounding
- Coordinate system rotation
- Scaling
- Cylindrical interpolation
- Helical interpolation (Circular interpolation plus Max. 2 axes linear interpolation)
- Polar coordinate command
- Circular interpolation (Multi-quadrant is possible)
- Programmable mirror image
- Background editing
- Extended editing
- Dynamic graphic display
- Nano interpolation
- Rigid tapping
- Multi language display
- Run hour and parts count display
- Automatic acceleration /deceleration
- Automatic corner override
- Rapid traverse: linear Cutting feed: exponential
- Tool offset pairs, ± 6 digits, 400 pairs
- Tool length compensation
- Tool offset memory C
- Part program storage length 1280 m
- Number of registered programs 400
- Self-diagnosis function
- Alarm history display
- Operation history display
- Help function
- Stored pitch error compensation
- Sub call
- Custom Macro B
- Additional custom macro variables
- Canned cycles for drilling
- Small hole peck cycle
- Tool life management
- Workpiece coordinate system, G52 - G59
- Addition of workpiece coordinate system 48 pairs
- Automatic tool length measurement
- Inch / Metric
- Embedded Ethernet

