

ITEMS		Model					
		CDE6140A	CDE6240A	CDE6150A	CDE6250A	CDE6166A	CDE6266A
Max swing diameter over bed		400mm 16"		500mm 20"		660mm 26"	
Max workpiece swing diameter over gap		--	700mm 27 1/2"	--	760mm 30"	--	910mm 35"
Machine bed guiderail width		394mm					
Effective length over gap		--	260mm 10 1/4"	--	260mm 10 1/4"	--	260mm 10 1/4"
Max workpiece length		750mm(30"); 1000mm(40"); 1500mm(60"); 2000mm(80"); 3000mm(120");					
Max cutting length		700mm(28"); 950mm(38"); 1450mm(57"); 1950mm(77"); 2950mm(116");					
Distance between spindle center and guiderail		220mm(8 5/8")		250mm(10")		325mm(13")	
Max workpiece swing diameter over tool post		220mm(8 5/8")		290mm (11 3/8")		430mm(16 15/16")	
Headstock	Spindle hole diameter	52mm(2") (Allowed processed bar diameter 50mm)					
	Spindle head	C6					
	Spindle hole front end taper	Morse 6#					
	Spindle speed step	22					
	Spindle speed range	11~1400rpm					
	Spindle torque	1586Nm					

中华人民共和国
THE PEOPLE'S REPUBLIC OF CHINA

大连机床集团有限责任公司
DALIAN MACHINE TOOL GROUP CORP.

普通车床
UNIVERSAL LATHE

型号
MACHINE MODEL

CDE6140A

规格
SPEC

1000

出厂编号
SER. NO.

12047

设备规格

CDE6140C/1000

设备编号

HJ08-J200-059

长沙黑金刚实业有限公司