

A4-HS FEATURES




1 Patented Double Pump Double Nozzle

Super high accuracy:
1/2000Y(0.015ml)
Suitable for sample
paint dispensing



2 100% Recirculation

Zero nozzle
dryness/blockage;
Purge-free;
Maintenance-free;
Colorant saving;
Stable accuracy;
Suitable for Z-VOC
colorant.



3 Ergonomical Filling Height

Suitable filling height makes easy operation.

4 Weight Feedback Function Optional

Electronic scale real-time feedbacks
dispensing amount. Accurate compensation
can be achieved according to feedback value.
It applies to industrial paint, ink, automotive
paint, etc.

5 Optional large channel industrial pump to adapt to fluids with higher viscosity



P1.1 Piston Pump Sequential Dispensing

■ Efficiency 500ml/min
※ It depends on the product property

■ Minimum Shot
1/2000Y (0.015ml)

■ Pump Capacity 100ml
■ Stirring Speed 20-25rpm

■ Canister Size 2.3L /3.8L

■ No. of Canisters Up to 16

■ Electrical Can Table (Optional)

■ Can Size (D X H) Electrical 320 X 390mm Manual 320 X 410mm

■ Machine Dimension (W X D X H) 720 X 885 X 1130-1200mm

■ Packing Dimension (W X D X H) 800 X 990 X 1360mm

■ 14 pcs/20GP 28 pcs/40GP

■ Net Weight Electrical 200kg, Manual 170kg

■ Gross Weight Electrical 250kg, Manual 220kg

■ Power Electrical 450W, Manual 350W

■ Power Supply 220V/110V 50Hz/60Hz

A4-HS Technical Parameters

