



GREENGINES INDUSTRIAL CO., LTD

Address: HUAXIN Machinery Store, Dongguang City Guangdong Province, China; Jim: +86 13544043705

PROFORMA INVOICE

PI date: 2023/08/06

validity: 2023/09/30

PI2023050020

Paya Trade Idea
Att: ID No.:
14011520273

Add:#33, Build. No. 1, Hosseinieh Alley, Dollat St.Tehran-IRAN CEO: Ehsan
Taghizadeh
Mobile: +98-9121866029

No.	Item	Description	QTY	Unit	unit price (Eu)	total price (Eu)
1	EM80-V	Chen Hsong brand 80ton Injection Molding machine	1	set	\$3,400.00	€ 3,400.00
2	MA900	Hitian 90ton injection molding Machine	2	set	\$4,100.00	€ 8,200.00
3	MA1200	Hitian 120ton injection molding Machine	2	set	\$6,750.00	€ 13,500.00

total value: € 25,100.00

Shipping: € 7,600.00

sub total: € 32,700.00



Remarks

- 1 Payment term: T/T
- 2 Trade Term: CIF
- 3 Payment Term: 100% IN ADVANCE
- 4 HS Code: 84771000

Bank Details

BENEFICIARY: HSBC Hong Kong
BENEFICIARY ADD. 1 Queen's Road Central,Hong Kong
SWIFT BIC HSBCHKHHHKH
BENEFICIARY NAME: GREENGINES INDUSTRIAL CO.,LIMITED
A/C: 801-143272-838
BENEFICIARY ADDRESS NO 1 QUEEN' S ROAD,CENTRAL,HONGKONG

Shipping Partial Shipment

Michael
Crong

0000001

GREENGINES INDUSTRY CO., LTD

Add: Fenggang Machinery Store, Dongguan City Guangdong Province, China 518103;



Injection Unit	MA900
Screw diameter (mm)	36
Screw L/D ratio (L/D)	20
Shot size (theoretical) (cm ³)	153
Injection Weight (PS) (g)	139
Injection rate (PS) (g/s)	108
Injection pressure (MPa)	196
Plasticizing rate (PS) (g/s)	12.6
Screw speed (rpm)	0-290
Clamping Unit	
Clamping force (kN)	900
Mold opening stroke (mm)	320
Dist. between tie bars (HxV) (mm)	360x360
Mold height max(mm)	380
Mold height min(mm)	150
Ejector stroke (mm)	100
Ejector force (kN)	33
Others	
Max. Pump Pressure	16
Pump motor power (kW)	13
Heater power (kW)	6.3
Machine dimension (l x w x h)	4.4x1.13x1.91
Machine weight (t)	3.5
Hopper capacity (kg)	25
Oil tank capacity (l)	190



Injection Unit	MA1200
Screw diameter(mm)	40
Screw L/D ratio (L/D)	21
Shot size (theoretical) (cm ³)	214
Injection Weight (PS) (g)	195
Injection rate (PS) (g/s)	139
Injection pressure (MPa)	192
Plasticizing rate (PS) (g/s)	15.4
Screw speed (rpm)	0-270
Clamping Unit	
Clamping force (kN)	1200
Mold opening stroke (mm)	360
Dist. between tie bars (HxV) (mm)	410x410
Mold height max(mm)	450
Mold height min(mm)	150
Ejector stroke (mm)	120
Ejector force (kN)	33
Others	
Max. Pump Pressure	16
Pump motor power (kW)	15
Heater power (kW)	9.95
Machine dimension (l x w x h)	4.88x1.20x2.03
Machine weight (t)	4.35
Hopper capacity (kg)	25

EM80



	Oil tank capacity (l)	255
ITEM	UNIT	EM 80
Swept volume	cm ³	163
Shot weight	g	150
Screw diameter	mm	36
Injection pressure(Max)	Kgf/cm ²	1561
Screw L/D ratio	mm	19.6
Screw stroke	mm	160
Screw rotation speed(Max)	rpm	170
Moulding clamping force(Max)	t	80
Opening stroke	mm	320
Space between tie bars(H X V)	mm	355 x 300
Maximum Daylight	mm	640
Mould thickness(Min-Max)	mm	130-320
Ejector stroke	mm	80
Ejector force(Max)	t	2.3
System pressure	Kgf/cm ²	148
Pump motor power	kw	7.5
Heating capacity	kw	6.5
Temperature control zones		3+Nozzle
Dry cycle time	s	1.6
Oil tank capacity	liter	170
Machine dimensions(L x W x H)	m	3.9 x 1.1 x 1.7
Machine weight	t	2.8