

Date :28/04/2023

Ref.No.: TPCO/TO/100519989

No.of Pages : 2

Technical Offer- Inquiry No.: 100519989

Customer: NICICO

Supplier : Tatra Parts s.r.o

Manufacturer: SEW

Speed [r/min]	: 1500 / 31
Total ratio [i]	: 49.16 / infinite
Ma max [Nm]	: 2700
Mounting position	: M1A
Lubricant / -volume [l]	: CLP HC 220 Synth.Oil / 3.70
Oil manufacturer designation	: Mobil SHC 630
Rotation	: Clockwise (view onto output shaft end)
Corrosion protection	: Yes
Extended storage	: Yes
Surface protection	: OS3 to technical data sheet 01802_94
Paint coat	: Top coat RAL7031 (blue gray)
Gear unit	: KH87/T
Ma max G [Nm]	: 2700
Hollow shaft	: 65mm
Design	: Hollow shaft with shrink disc
Anti-corrosion agent [l]	: 0.01
Output oil seal	: 2 oil seals FKM
Number of oil sight glasses	: 1
Position of oil sight glass 1	: B41
General access. feature	: T with torque arm
Screw plug bore dimens. sheet	: 33140_09
Documentation no. A	: 27801578
Parts list	: 382632395



Adapter	: AMS132S/M/RS
Output oil seal material	: Oil seal made of FKM with optimized spring force
Input flange	: Centering diameter 230mm, hole circle 265mm, thread M12
Bore on input side	: 38mm
Max. insertion depth (mot. SE)	: 80mm
Access. feature backstop	: RS Backstop
Nameplate	: English
Nameplate position	: Attached to the gear unit
Text of gear unit nameplate	: right rotation
Opera.instr. A lang./quantity	: SK

This offer has been prepared electronically and it is valid without signature and stamping.

We remain at your disposal for any further information you may need on above technical offer . Many thanks in advance for your feedback,

Yours faithfully

Sales team - Tatra parts s.r.o

Pezinská 901/ 5 , Chorvatsky Grob , 90025 , Slovakia