



亚东集团 SINCE 1976
YADONG GROUP

中国青岛亚东机械集团



QINGDAO YADONG MACHINERY GROUP CO.,LTD



ADD: NO.517 Changjiang Middle Road, ETDZ, Qingdao, 266555, Shandong Province, CHINA

Tel: +86 532 8699 8653, +86 532 8586 1583 Fax: +86 532 6897 2933 Skype: chinaweidong2000

H.P: +86 186 7861 5565 E-mail: eric@yatongroup.com ; Info_yadong@163.com http://www.yadong-rm.com

PROFORMA INVOICE

Proforma NO.: 23YFO1

DATE: NOV 20 , 2023

TO: Yazd Faravahar Oil seal Company - ID:14009753190

Validity Date:Nov,20,2024

SHIPMENT: FROM: Qingdao,China

TO: Bandar Abbas,Iran

Goods Description	MODEL	QTY	UNIT PRICE	AMOUNT
<p>Rubber Rolling Mixer</p> 	<p>XK-φ300*750 Roller Mixer</p>	<p>1SET</p>	<p>EUR 8600</p>	<p>EUR 8600</p>
<p>Kneader</p> 	<p>X(S)N-25L Kneader</p>	<p>1SET</p>	<p>EUR 9700</p>	<p>EUR 9700</p>
	<p>XQL-600 Rubber Bale cutter</p>	<p>1SET</p>	<p>EUR 1200</p>	<p>EUR 1200</p>

<p>Skeleton Oil Seal Press</p> 	<p>Volcunize Rubber press 150 Ton</p>	<p>1SET</p>	<p>EUR 5850</p>	<p>EUR 5850</p>
	<p>SC-600 Rubber Cutter</p>	<p>1SET</p>	<p>EUR 1450</p>	<p>EUR 1450</p>
<p>TOTAL AMOUNT (FOB QINGDAO, CHINA) Sea freight Total C&F</p>				<p>EUR 26800 3000 Total EUR 29800</p>

BENEFICIARY: QINGDAO JUDONG INDUSTRY CO., LTD

NAME OF BANK: BANK OF CHINA QINGDAO BRANCH, QINGDAO ECONOMIC AND TECHNICAL DEVELOPMENT ZONE SUB-BRANCH

BANK ADDRESS: NO.65, XIANGJIANG ROAD, QINGDAO ECONOMIC AND TECHNICAL DEVELOPMENT ZONE, 266555 , CHINA.

ACCOUNT NUMBER: 228604391163

SWIFT CODE: BKCHCNBJ50A

REMARK: QINGDAO JUDONG INDUSTRY CO., LTD Is the subsidiary company and the professional exporting department of YADONG GROUP. It is mainly in charge of the exporting working for YADONG GROUP.

CONFIRMED BY BUYER:

CONFIRMED BY SELLER:



<< MACHINERY DESCRIPTIONS >>

RUBBER ROLLING MIXER (RUBBER MIXING MILL)

MODEL: XK-300*750 (12 inch diameter)

1.Main Technical Parameters:

NO.	MODEL	XK-Ø300 (12")
1	Working diameter of rolls	Ø300 mm
2	Working length of rolls	750mm
3	Working linear speed of front roll	15.7m/min (can be designed as per your customized requirement)
4	Friction ratio of front and rear rolls	1: 1.25 (can be designed as per your customized requirement)
5	Max gap range	0~10mm
6	Capacity per batch	15~20kg
7	Driving motor power	22KW(AC)
8	Bearings of mixing rollers	Rolling bearing
9	Lubricating mode	Grease/Oil lubrication
10	Nip adjustment method	Manual
11	Power supply	As per Customer's demand
13	About weight	5500kg

KNEADER

MODEL: X(S)N-25L

1. Stock pressing device	1 set
2. Rack	1 set
3. Mixing device	1 set
4. Tilting device	1 set
5. Reducer	1 set
6. Support	1 set
7. Belt transmission device	1 set
8. Pneumatic control system.	1 set
9. Heating and cooling system	1 set
10. Support of limit	1 set
11. Base	1 set
12. Main motor	1 set
13. Electric control cabinet and operation station	1 set
14. Dusting outlet	1 set
15. Full set of technical documents	2 sets
1. Total volume of mixing chamber:	45L
2. Working volume of mixing chamber:	25L
3. Rotational speed of rotors:	34/28
4. Pressure of compressed air:	0.6~0.8 MPa
5. Pressure of cooling water:	0.2~0.4 Mpa
6. Pressure of heating steam:	0.5~0.8 Mpa
7. Tilting angle of mixer chamber:	140°
8. Driving part:	
Main motor	
Power:	30 Kw (AC)
Voltage:	As per customer demand
Hydraulic tilting motor	
Power:	3 Kw
Voltage:	As per customer demand
9. Overall dimension:	2560X1650X2500 (mm)
10. About weight:	~ 5000kg

SKELETON OIL SEAL PRESS

MODEL:150T


1. Main Technical Parameters:

NO.	Technical Parameter	150T	Remarks
1	Nominal mold clamping force	150Ton	
2	Heating plate specifications	Upper heating plate: 420mm×460mm	Formwork board: 410mm*475mm
3		Down heating plate: 420mm*460mm	
4	Number of hot plates	2pcs	
5	heating method	Electric heating	0-250°C
6	Temperature control method	Smart digital display	Smart digital display temperature
7	Piston diameter	Φ320mm	Material: Chilled alloy
8	Number of cylinders	1SET	
9	Hot plate spacing	200mm	
10	Master cylinder maximum stroke	200mm	
11	big pillar	φ 80mm	
12	System usage pressure	20Mpa	
13	structure type	Four column	
14	control method	PLC Control	China brand
15	Pressure setting method	Pressure sensor control	
16	Motor Power	5.5KW	China brand
17	total heating power	10KW	
18	Machine weight	3000KG	

RUBBER CUTTING MACHINE

MODEL:SC-600

MAIN TECHNICAL PARAMETERS:

Equipment Name	SC-600 CNC rubber sheet slitting&cutting machine	
Voltage	380v 50Hz	 Internal structure
Cutting width(max.)	600 mm	
Cutting thickness(max.)	20 mm	
Crosscutting range	0 ~ 9999 mm	
Cutting range	25 ~ 600 mm	
Cutter material	High quality Inlaid edge steel	
Slitting circular blade quantity	25 PCS	
Cross-cut size adjustment method	Touch screen by PLC control.	
Cutting size adjustment method	manual adjustment	
Crosscut motor power	1.5kw+ reducer	
Slitting servo motor	1.8kw (servo motor) + reducer	
Weight	700 kg	
Dimensions	1100×1200×1400 mm	

RUBBER BALE CUTTER

MODEL: XQL-600

Main Technical Parameters:

NO.	MODEL	XQL-600
1	Power Supply	According to customer's demand
2	Cutting width	660mm
3	Stroke	600mm
4	Total Pressure	30Ton
5	Main motor power	5.5kw
6	Cutting speed	10-50 times/minute
7	Knife materials	Hard Alloy Steel
8	Overall dimensions	1200×1200×2100 (mm)