

Standard Equipment/Optional Equipment

Standard Equipment

Open cabin with armoured glass roof	Engine intake air cleaner with integral safety element
Adjustable steering column	ZF 3 WG 161/ZF 3 WG 131 ERGOPOWER SERIES (depending on the truck model)
Orange lap type seat belt	Kessler D81 drive axle
USB charging port	Digital, proportional valve with integrated safety monitoring
Battery isolator switch	High-performance hydraulic filter preserving max. purity of oil for long life of all hydraulic components
Abundant storage space	Undertrays on chassis
Chassis mounted hourmeter	Fork carriage, width b3=2545 mm
12V socket in cabin	Trelleborg or similar premium tyres
Lockable, underseat storage box	Standard mast, lift height h3 = 4000 mm
Single drive pedal with direction selector in armrest	Linde Service Monitoring System incl. static and mobile working hours
Basic PVC covered seat	
Linde Load Control for low-effort precision of all mast functions	
Armrest with storage box	
4.3" High resolution colour display	
Electro-hydraulic forward tilting cabin	
Audible warning reverse alarm (85 dB)	

Optional Equipment

Fully cabin with clear, tinted or heated glass and armoured glass roof	Remote (Modem) diagnostics
External rear view mirrors	Absent driver shut off switch
Internal mirror/Panoramic internal mirror	Connect Access Control
Buddy seat, PVC covered	Individual levers for lift and tilt/forkspread and sideshift
10° or 17° rotating driver's seat	Digital audio broadcasting radio with MP3, USB, Bluetooth and speakers
DIN A4 illuminated clipboard	Truck speed limiting based on digital input (switch inside the cabin)
Cup holder	Cyclonic air intake filter
Heater/Climate Control	Single and double auxiliary hydraulics for all mast types
Sun blinds front & top screen	Linde Load Weight Indicator (+/- 100 kg)
Cabin pre-heater	Mast accumulator
Reversing camera system and screen	Integral fork positioner
Active radar system	Michelin and Simex E4 tyres
Seat incorporating air suspension with compressor	Standard masts, 2430 - 9500 mm lift height (model specific, refer to mast table)
Gated lever - additional hydraulic service	Duplex masts (full free lift), 2580 - 7000 mm lift height (model specific)
External step lighting	Custom paintwork
Working lights LED	Triplex masts (full free lift), 5500 - 7000 mm lift height
Full road lighting	Variable displacement piston pump
Beacon lamps	
7" colour display with „rotary pushbutton knob“ for ergonomic menu navigation	