

ITEM	DESCRIPTION	MATERIAL
1	ELBOW 45° , <u>SIZE 8"</u> ,LR C.S A234/WPB ,SEAMLESS ASME B16.9 BUTTWELDING BEVELLED END, <u>SCH. STD</u> , NACE MR0175/ISO 15156	A234/WPB NACE MR0175/ISO 15156 (HARDNESS <197HB NO S LIMITATION)
2	ELBOW 90° , <u>SIZE 8"</u> ,LR C.S A234/WPB ,SEAMLESS ASME B16.9 BUTTWELDING BEVELLED END, <u>SCH. STD</u> , NACE MR0175/ISO 15156	A234/WPB NACE MR0175/ISO 15156 (HARDNESS <197HB NO S LIMITATION)
3	ELBOW 90° , <u>SIZE 6"</u> ,LR C.S A234/WPB ,SEAMLESS ASME B16.9 BUTTWELDING BEVELLED END, <u>SCH. STD</u> , NACE MR0175/ISO 15156	A234/WPB NACE MR0175/ISO 15156 (HARDNESS <197HB NO S LIMITATION)
4	ELBOW 45 DEGREE , <u>SIZE 6"</u> ASME B16.9 SEAMLESS C.S ASTM A860/WPHY 60 BUTTWELDING <u>SCH STD</u>	ASTM A860/WPHY 60
5	ELBOW 45 DEGREE , <u>SIZE 8"</u> ASME B16.9 SEAMLESS C.S ASTM A860/WPHY 60 BUTTWELDING SCH STD	ASTM A860/WPHY 60
6	ELBOW 45 DEGREE , <u>SIZE 10"</u> ASME B16.9 SEAMLESS C.S ASTM A860/WPHY 60 BUTTWELDING <u>SCH STD</u>	ASTM A860/WPHY 60
7	ELBOW 45 DEGREE , <u>SIZE 12"</u> ASME B16.9 SEAMLESS C.S ASTM A860/WPHY 60 BUTTWELDING <u>SCH STD</u>	ASTM A860/WPHY 60
8	TEE EQUAL <u>SIZE 6"</u> ASME B16.9 SEAMLESS C.S ASTM A860/WPHY 60 BUTTWELDING <u>SCH STD</u>	ASTM A860/WPHY 60
9	TEE EQUAL <u>SIZE 8"</u> ASME B16.9 SEAMLESS C.S ASTM A860/WPHY 60 BUTTWELDING <u>SCH STD</u>	ASTM A860/WPHY 60
10	TEE EQUAL <u>SIZE 10"</u> ASME B16.9 SEAMLESS C.S ASTM A860/WPHY 60 BUTTWELDING <u>SCH STD</u>	ASTM A860/WPHY 60
11	TEE REDUCING <u>6"X6"X4"</u> ASME B16.9 BUTTWELDING CARBONSTEEL A234/WPB SEAMLESS NACE MR0175/ISO 15156 <u>SCH. STD X STD</u>	A234/WPB NACE MR0175/ISO 15156 (HARDNESS <197HB NO S LIMITATION)
12	<u>4*6</u> "CONCENTRIC REDUCER ASME16.9 SEAMLESS C.S ASTM-A860/WPHY 60 BUTT WELDING <u>SCHSTD* STD</u>	ASTM A860/WPHY 60

ITEM	DESCRIPTION	MATERIAL
13	<u>4"8"</u> CONCENTRIC REDUCER ASME16.9 SEAMLESS C.S ASTM-A860/WPHY 60 BUTT WELDING <u>SCHSTD* STD</u>	ASTM A860/WPHY 60
14	<u>6"8"</u> CONCENTRIC REDUCER ASME16.9 SEAMLESS C.S ASTM-A860/WPHY 60 BUTT WELDING <u>SCHSTD* STD</u>	ASTM A860/WPHY 60
15	<u>6"10"</u> CONCENTRIC REDUCER ASME16.9 SEAMLESS C.S ASTM-A860/WPHY 60 BUTT WELDING <u>SCHSTD* STD</u>	ASTM A860/WPHY 60
16	<u>8"10"</u> CONCENTRIC REDUCER ASME16.9 SEAMLESS C.S ASTM-A860/WPHY 60 BUTT WELDING <u>SCHSTD* STD</u>	ASTM A860/WPHY 60
17	<u>6"12"</u> CONCENTRIC REDUCER ASME16.9 SEAMLESS C.S ASTM-A860/WPHY 60 BUTT WELDING <u>SCHSTD* STD</u>	ASTM A860/WPHY 60
18	<u>8"12"</u> CONCENTRIC REDUCER ASME16.9 SEAMLESS C.S ASTM-A860/WPHY 60 BUTT WELDING <u>SCHSTD* STD</u>	ASTM A860/WPHY 60
19	<u>10"12"</u> CONCENTRIC REDUCER ASME16.9 SEAMLESS C.S ASTM-A860/WPHY 60 BUTT WELDING <u>SCHSTD* STD</u>	ASTM A860/WPHY 60

PROFORMA INVOICE

TO: RADIATOR DERAKHSHAN JONOBB
 ADD: TALASH 7 STREET ,NO:2 INDUSTRIAL ZONE, AHVAZ, IRAN

PI NO.: CH22090101
 DATE: Sept 1st, 2022
 VALIDITY : SEP 1ST 2024

1.PRICE, SCOPE OF SUPPLY & SPECIFICATIONS , HS CODE 73079300

ITEM	UNIT	DESCRIPTION	QUANTITY	PRODUCT	OD INCH	WT	MATERIAL	STANDARD	Unit Weight KG/PC	Total Weight KG	Unit Price EURO/PC	Total Price EURO
1	NO	8 " ELBOW 45° LR C.S A234/WPB SEAMLESS ASME B16.9 BUTTWELDING BEVELLED END, SCH STD NACE MR0175/ISO 15156	15	45 LR ELBOW SMLS	8	STD	A234/WPB NACE MR0175/ISO 15156 (Hardness ≤197HB No S limitation)	B16.9	10.98	164.7	22.61	339.15
2	NO	8 " ELBOW 90° LR C.S A234/WPB SEAMLESS ASME B16.9 BUTTWELDING BEVELLED END, SCH STD NACE MR0175/ISO 15156	10	90 LR ELBOW SMLS	8	STD	A234/WPB NACE MR0175/ISO 15156 (Hardness ≤197HB No S limitation)	B16.9	21.96	219.6	37.53	375.3
3	NO	6" ELBOW 90° LR C.S A234/WPB SEAMLESS ASME B16.9 BUTTWELDING BEVELLED END, SCH STD NACE MR0175/ISO 15156	10	90 LR ELBOW SMLS	6	STD	A234/WPB NACE MR0175/ISO 15156 (Hardness ≤197HB No S limitation)	B16.9	11.21	112.1	17.56	175.6
4	NO	6" ELBOW 45 DEGREE ASME B16.9 SEAMLESS C.S ASTM A860/WPHY 60 BUTTWELDING SCH STD	4	45 LR ELBOW SMLS	6	STD	ASTM A860/WPHY 60	B16.9	5.6	22.4	10.59	42.36
5	NO	8" ELBOW 45 DEGREE ASME B16.9 SEAMLESS C.S ASTM A860/WPHY 60 BUTTWELDING SCH STD	4	45 LR ELBOW SMLS	8	STD	ASTM A860/WPHY 60	B16.9	10.98	43.92	22.6	90.4
6	NO	10" ELBOW 45 DEGREE ASME B16.9 SEAMLESS C.S ASTM A860/WPHY 60 BUTTWELDING SCH STD	4	45 LR ELBOW SMLS	10	STD	ASTM A860/WPHY 60	B16.9	19.4	77.6	42.1	168.4
7	NO	12" ELBOW 45 DEGREE ASME B16.9 SEAMLESS C.S ASTM A860/WPHY 60 BUTTWELDING SCH STD	4	45 LR ELBOW SMLS	12	STD	ASTM A860/WPHY 60	B16.9	28.19	112.76	61.34	245.36
8	NO	6" TEE EQUAL ASME B16.9 SEAMLESS C.S ASTM A860/WPHY 60 BUTTWELDING SCH STD	4	EQUAL TEE SMLS	6	STD	ASTM A860/WPHY 60	B16.9	11.76	47.04	62.55	250.2
9	NO	8" TEE EQUAL ASME B16.9 SEAMLESS C.S ASTM A860/WPHY 60 BUTTWELDING SCH STD	4	EQUAL TEE SMLS	8	STD	ASTM A860/WPHY 60	B16.9	20.55	82.2	91.41	365.64
10	NO	10" TEE EQUAL ASME B16.9 SEAMLESS C.S ASTM A860/WPHY 60 BUTTWELDING SCH STD	4	EQUAL TEE SMLS	10	STD	ASTM A860/WPHY 60	B16.9	34.34	137.36	156.37	625.48
11	NO	TEE REDUCING 6"x6"x4" ASME B16.9 BUTTWELDING CARBONSTEEL A234/WPB SEAMLESS NACE MR0175/ISO 15156 SCH STD X STD	10	REDUCING TEE SMLS	6x4	STD	A234/WPB NACE MR0175/ISO 15156 (Hardness ≤197HB No S limitation)	B16.9	9.95	99.5	57.731	577.31
12	NO	4*6 "CONCENTRIC REDUCER ASME16.9 SEAMLESS C.S ASTM-A860/WPHY 60 BUTT WELDING SCHSTD* STD	5	CONCENTRIC REDUCER SMLS	6x4	STD	ASTM A860/WPHY 60	B16.9	3.96	19.8	14.44	72.2
13	NO	4*8 "CONCENTRIC REDUCER ASME16.9 SEAMLESS C.S ASTM-A860/WPHY 60 BUTT WELDING SCHSTD* STD	5	CONCENTRIC REDUCER SMLS	8x4	STD	ASTM A860/WPHY 60	B16.9	6.47	32.35	21.65	108.25
14	NO	6*8 "CONCENTRIC REDUCER ASME16.9 SEAMLESS C.S ASTM-A860/WPHY 60 BUTT WELDING SCHSTD* STD	5	CONCENTRIC REDUCER SMLS	8x6	STD	ASTM A860/WPHY 60	B16.9	6.47	32.35	18.05	90.25
15	NO	6*10"CONCENTRIC REDUCER ASME16.9 SEAMLESS C.S ASTM-A860/WPHY 60 BUTT WELDING SCHSTD* STD	5	CONCENTRIC REDUCER SMLS	10x6	STD	ASTM A860/WPHY 60	B16.9	10.74	53.7	36.08	180.4
16	NO	8*10"CONCENTRIC REDUCER ASME16.9 SEAMLESS C.S ASTM-A860/WPHY 60 BUTT WELDING SCHSTD* STD	5	CONCENTRIC REDUCER SMLS	10x8	STD	ASTM A860/WPHY 60	B16.9	10.74	53.7	33.68	168.4
17	NO	6*12"CONCENTRIC REDUCER ASME16.9 SEAMLESS C.S ASTM-A860/WPHY 60 BUTT WELDING SCHSTD* STD	5	CONCENTRIC REDUCER SMLS	12x6	STD	ASTM A860/WPHY 60	B16.9	15	75	52.92	264.6
18	NO	8*12"CONCENTRIC REDUCER ASME16.9 SEAMLESS C.S ASTM-A860/WPHY 60 BUTT WELDING SCHSTD* STD	5	CONCENTRIC REDUCER SMLS	12x8	STD	ASTM A860/WPHY 60	B16.9	15	75	46.91	234.55
19	NO	10*12"CONCENTRIC REDUCER ASME16.9 SEAMLESS C.S ASTM-A860/WPHY 60 BUTT WELDING SCHSTD* STD	5	CONCENTRIC REDUCER SMLS	12x10	STD	ASTM A860/WPHY 60	B16.9	15	75	45.23	226.15
SEA FREIGHT												1000
TOTAL			113						NET W	1536.08		5600
										GROSS W	1700	

- Price: EURO/PC, CFR BANDAR ABBAS
- Lead time: 35 days since receipt of advanced payment.
- Packing: Black varnish, with end protecters, Sea worthy packages.
- Payment terms: 30% advance payment, 70% before shipment
- Documents: Mill Test Certificate (EN 10204 - 3.1), B/L, Packing List, Invoice.
- Mode of transportation: by Sea.
- Loading port: Tianjin Port, China.
- TPI Accepted, but the charge of TPI will be borne by buyer.

2.BANK INFORMATION

Beneficiary's Bank:
 BANK OF COMMUNICATIONS OBU
 SWIFT NO: COMMCN3XOBU
 ADDRESS: 1ST FLOOR, NO.188, YINCHENG ZHONG ROAD, PUDONG, SHANGHAI 200120
 Beneficiary' AC & Name:
 A/C NO: 90000095444100
 NAME: HEBEI CANGHAI HEAVY INDUSTRY CO., LTD