

技术参数 Technical Parameter

CY-MH103A无人化打包机Fully auto packaging machine

1. 电源、功率 Power: 380V, 50/60Hz
2. 捆包速度: 2.2秒/道 2. Bundling speed: 2.2 seconds per track
3. 弓架内尺寸: W900*H1000mm 3. Inner size of bow frame: W900 * H1000mm
4. 捆紧力: 5-80kg 4. Binding force: 5-80kg
5. 适用带宽: 厚: 0.5-1.2mm 宽: 9、11.5、12、13.5、15 (±1) mm选一种
5. Applicable bandwidth: thickness: 0.5-1.2mm, width: 9, 11.5, 12, 13.5, 15 (± 1) mm, can choose one of them
6. 弓架内框距地面: 200mm (可根据客户需要定制)
6. Distance between the inner frame of the bow frame and the ground: 200mm (customizable according to customer needs)
7. 产品重量: 50KG
7. Net weight: 50KG
8. 机械尺寸: 2200*620*140mm
8. Machine dimension: 2200*620*140mm
9. 重量: 255kgs
9. Weight: 255kgs
10. 侧口位置: 在产品侧面
10. Side opening position: on the side of the product
11. 捆扎形式: 方式有手动, 平行自动同一方向1-2道
11. Binding form: There are manual and parallel automatic modes, with 1-2 lanes in the same direction
12. 电器配置: 12. Electrical configuration:
PLC: 西门子 S7-200 PLC: Siemens S7-200
交流接触器: 法国(施耐德) AC contactor: France (Schneider)
热保护器: 法国(施耐德) Thermal protector: France (Schneider)
继电器: 欧姆龙 Relay: Omron
变压器: 联创电气 Transformer: Lianchuang Electric
光电形式: 慢反射 Optoelectronic form: slow reflection
按钮开关: 德国(西门子APT) Button switch: Germany (Siemens APT)
电机: MEI WA (370W) Motor: MEI WA (370W)
13. 机身材质: Q235A钢; 13. Body material: Q235A steel;
机身表面处理: 喷塑处理 Surface treatment of the body: spray plastic treatment
14. 产品颜色: 白色 Color: White

此图片仅供参考, 请以实际为准!

