



❖ Automatic Packing Line

BL-P202-SHS

Automatic Packing Line is used for packing finished brake pads, brake linings and all the finished or semi-finished products by film shrinking, box taping and belting automatically.

● **Technical Parameters:**

➤ **POF Bagging Machine BL-P202-PBM**

- ◆ Power supply: 16A,3.5KW
- ◆ Pressure: 5-7KG/CM2
- ◆ Pacing Speed: 0-20 bags/min.
- ◆ Table Height: 780mm
- ◆ Object Max. Size: 500x400x150mm,
- ◆ Object W+H ≤ 470mm, Object H ≤ 150mm
- ◆ Deliver Speed: 20m/min
- ◆ Sealing Knife Material: Stainless Steel;
- ◆ Heating Unit: 2 x 1000W
- ◆ Cutting Film and sealing Time: < 1.5 s
- ◆ Sealing Temperature: 150-230°C
- ◆ POF Film Thickness: 0.015-0.019mm
- ◆ Machine Weight: 420kg
- ◆ Machine Size (mm):1670 × 766 × 1515 mm

➤ **Tape Sealing Machine BL-P202-TSM**

- ◆ Working table height: 550-750mm (adjustable)
- ◆ Sealing speed: 19 m/min.
- ◆ Box Size: L ≥ 150mm; W 120-480mm; H 120-480mm
- ◆ Sealing tape: kraft paper tape, BOPP tape
- ◆ Tape size: 48-72mm
- ◆ Weight: 100kg

➤ **Shrinking Tunnel Oven BL-P202-PSO**

- ◆ Power: 12-36KW (adjustable)
- ◆ Conveying speed: 0-18 m/min (adjustable)
- ◆ Worktable height: 750 mm (can be customized)
- ◆ Temperature control range: 0-400°C (adjustable)
- ◆ Use range: 100-180°C

➤ **Baler Machine BL-P202-BM**

- ◆ Power supply: 1.27KW/5A
- ◆ Width 800mm×height 600 mm (can be customized)
- ◆ Worktable height: 750 mm (can be customized)
- ◆ Packing speed: ≤ 2.5 seconds/track
- ◆ Tightening force: 0-90kg (adjustable)
- ◆ Binding form: 1-3 lanes, photoelectric or manual.
- ◆ Packing Belt W: 9-15 mm, T 0.55-1.0 mm
- ◆ Product size: L (≥ 200) (300 ≤ W ≤ 700) H (≤ 500) mm



POF Bagging Machine



Shrinking Tunnel Oven



Tape Sealing Machine



Baler Machine