

Item No.

فهرست تجهیزات و خدمات

E	Engineering
E-1	Engineering
C	Construction
C-1	Construction
P	Procurement
P-1	HFC227 Gas Extinguishing System to protect: SERVER ROOM
P-1-1	HFC 227 Fire-fighting system Including:
P-1-2	5 x 120 Lit Manifold system C/W RGS-MAM-40 Cylinder valve , FH-40HC 1 1/2" G Cylinder Hose , Check valve VALAN-40-23 , System cylinder bracket , Instructions cylinder sticker , CE marking cylinder sticker , PI marking cylinder sticker , Bridle
P-1-3	Pneumatic actuator P.N : 227CN
P-1-4	"T" or elbow P.N : 1/4"G
P-1-5	Flexible actuator hose P.N : FH-6PO 1/4"G (500 mm)
P-1-6	Kg of extinguishing agent Dupont FM200 P.N : 200KG
P-1-7	مجموعة cylinder c/w مجموعة cylinder bracket , Bridle , Pressure gauge P.N : S140-P200
P-1-8	مجموعة cylinder valve P.N : RGS-MAM-11/4
P-1-9	Re-assembled electrical actuator head P.N : 227SOL
P-1-10	Manual actuator head P.N : 227DM
P-1-11	Discharge manifold
P-1-12	Pressure switch P.N : POINPRE
P-1-13	Discharge Nozzle
P-1-14	RADIAL NOZZLE 360° 1/2" MODEL FEDR15 UL/FM APPROVED
P-1-15	PLATE CALIBRATE 1/2" MODEL POPC15 UL/FM APPROVED
P-1-16	RADIAL NOZZLE 360° 1 1/2" MODEL FEDR40 UL/FM APPROVED
P-1-17	PLATE CALIBRATE 1 1/2" MODEL POPC40 UL/FM APPROVED
P-2	HFC227 Gas Extinguishing System to protect: POWER ROOM
P-2-1	HFC 227 Fire-fighting system Including:
P-2-2	MODULAR CYLINDER 120L SYSTEM SIEX-HC 227-25 BAR UL/FM APPROVED Modular cylinder 180L pressurized with dry nitrogen with a charge pressure of 25bar@20°C. Equipped with RGS-MAM-50 valve, built with brass, with bursting disc and control pressure gauge model UF40H-P25 (UL/FM). It also includes drill tube, bridle, protector cap and transport accessories. P.N : 227M120UF25
P-2-3	Kg of extinguishing agent Dupont FM200 P.N : 200KG
P-2-4	REARMABLE ELECTRIC ACTUATOR HEAD MODEL 227SOL 24 Vcc-DC UL/FM APPROVED
P-2-5	MANUAL ACTUATOR HEAD MODEL 227DM UL/FM
P-2-6	VERTICAL BRACKET MODEL HE120 FOR 120 LITERS (2 PER CYLINDER) UL/FM APPROVED
P-2-7	RIGID HOSE 2" MODEL FH-50HC UL/FM
P-2-8	CAUTION SIGN مجموعة
P-2-9	Discharge Nozzle
P-2-10	RADIAL NOZZLE 360° 1/2" MODEL FEDR15 UL/FM APPROVED
P-2-11	PLATE CALIBRATE 1/2" MODEL POPC15 UL/FM APPROVED
P-2-12	RADIAL NOZZLE 360° 1 1/2" MODEL FEDR40 UL/FM APPROVED
P-2-13	PLATE CALIBRATE 1 1/2" MODEL POPC40 UL/FM APPROVED
P-3	HFC227 Gas Extinguishing System to protect: UNPACKING ROOM
P-3-1	HFC 227 Fire-fighting system including:
P-3-2	MODULAR CYLINDER 120L SYSTEM SIEX-HC 227-25 BAR UL/FM APPROVED Modular cylinder 180L pressurized with dry nitrogen with a charge pressure of 25bar@20°C. Equipped with RGS-MAM-50 valve, built with brass, with bursting disc and control pressure gauge model UF40H-P25 (UL/FM). It also includes drill tube, bridle, protector cap and transport accessories. P.N : 227M120UF25
P-3-3	Kg of extinguishing agent Dupont FM200 P.N : 200KG
P-3-4	REARMABLE ELECTRIC ACTUATOR HEAD MODEL 227SOL 24 Vcc-DC UL/FM APPROVED

Item
No.

فہرست تجهیزات و خدمات

P-3-5	MANUAL ACTUATOR HEAD MODEL 227DM UL/FM
P-3-6	VERTICAL BRACKET MODEL HE120 FOR 120 LITERS (2 PER CYLINDER) UL/FM APPROVED
P-3-7	RIGID HOSE 2" MODEL FH-50HC UL/FM
P-3-8	CAUTION SIGN مجموعہ
P-3-9	Discharge Nozzle
P-3-10	RADIAL NOZZLE 360° 1/2" MODEL FEDR1S UL/FM APPROVED
P-3-11	PLATE CALIBRATE 1/2" MODEL POPC15 UL/FM APPROVED
P-3-12	RADIAL NOZZLE 360° 1 1/2" MODEL FEDR40 UL/FM APPROVED
P-3-13	PLATE CALIBRATE 1 1/2" MODEL POPC40 UL/FM APPROVED