



# SHANGHAI GIENI INDUSTRIES CO.,LTD

Floor 1-2, Building 3, No.1227 Xing Wen Road, Jiading District, Shanghai, China Tel:+86 21 39120276 Mob:86-13482060127

TO: Amin  
 EMAIL:  
 Offer NO.: JYH2023072702  
 COMPANY Swanhillsgroup

FROM: Ms. Joan Wu  
 EMAIL: joan.wu@genie-mail.net  
 DATE: 2023.7.27

**SUB: QUOTATION**

CUSTOMER REQUIREMENT: JSM HALF Silicone Lipstick Production Line

COMMERCIAL OFFER (INCOTERM: EXW FACTORY / WITHOUT VAT / WITH EXPORTING PACKING ) (IN USD)							
No.	Equipment Name	Model No.	QTY	Unit Price (USD)	Amount (USD)	Remarks	
<b>Half Silicone Lipstick Producing Equipment (2000-3600pcs/hour)</b> Process: Auto preheating mold--auto filling--auto reheating--Auto circulation Cooling--(manual take off upper mold, place case fitter, put on releasing machine)--Auto releasing--(Mold auto conveyed back to filling)--Auto Screw down--Manual QC and capping							
<b>SILICONE LIPSTICK FILLING PRODUCTION LINE</b>		<b>JSM</b>	<b>1</b>	<b>SET</b>			
-output:2400-3000 pcs/hour							
SCOPE OF SUPPLY:							
1.1	10 NOZZLES Lipstick Filling Machine -with Pre-heat and remelting device; -with conveyor.		1	SET			
1.2	Chilling Tunnel -7.5P chilling capacity, -Mold transfer in the tunnel		1	SET			
1.3	Lipstick Releasing Machine -Vacuum type; -with conveyor		1	SET			
1.6	Working Platform		1	SET			
1.7	10 Cavities Lipstick Mold aluminum#7075; Anodize processing		40	SET			
1.8	Upper mold remover		3	PCS			
1.9	Case fitter		3	PCS			
<b>SUB TOTAL</b>							
ACCESSORIES FOR MAKING SILICONE LIPSTICK							
1.10	Silicone PCS water drop; 12.1, standard mold; Mold open charge will be from 1500USD to 3000USD depends on shape		1000	PCS			
1.11	Lipstick Container Holder Customized according to the container		15	SET			
<b>TOTAL EXW FACTORY</b>						<b>EXCLUDE THE MOLD OPEN COST IF ANY</b>	

**GOODS DESCRIPTIONS**

**JSM HALF SILICONE LIPSTICK FILLING PRODUCTION LINE**




1.1. Lipstick Filling Machine JLG		CONFIGURATION:		HIGHLIGHTS:
<b>BASIC INFORMATION:</b>		Touch Screen: Weinview		<ul style="list-style-type: none"> <li>20L Three layer SUS304 tank, Inner layer is SUS316L; It has heating, mixing and vacuum function; Mixing Speed is adjustable.</li> <li>Piston type filling, driven by servo motor; Mold lifting adopts servo driven;</li> <li>Machine Frame is aluminum alloy and SUS304 material;</li> <li>Filling precision:±0.1g.</li> <li>Human-machine interface, touch screen control, easy operation;</li> <li>Photozell detect for auto filling;</li> <li>Adopts Switzerland Leister Gun for pre-heating, lamp pipe for remelting the shrinking hole after filling.</li> </ul>
Outer dimension: 1300X1050X2200mm (L*W*H)		PLC: Mitsubishi		
Voltage: AC220V, 1P, 50/60HZ		Servo Motor: Mitsubishi		
Power: 3.8KW		Cylinder: Airtac		
Air supply: 0.6-0.8Mpa, ≥300L/min		motor: JSSC		
Output: acc.to the container		Sensor: Omron		
Tank volume: 20L		Electric Element: Schneider or equivalent		
Weight: 260KG				




10 Nozzle Filling Machine



Mold Pre-heating



Nozzle heated, material tray






Re-heating







**TO:** Amin  
**EMAIL:**  
**Offer NO.:** JYH2023072702  
**COMPANY:** Swanhillsgroup

**FROM:** Ms. Joan Wu  
**EMAIL:** joan.wu@genie-mail.net  
**DATE:** 2023.7.27

1.2. Chilling Tunnel JCT		
BASIC INFORMATION:	CONFIGURATION:	HIGHLIGHTS:
Model JCT	Compressor: france brand	• Adopts France brand Compressor, environmental media R404A;
Outer dimension 3500x760x1400mm (LxWxH)	Electric Element: Schneider or equivalent	• Cooling time is adjustable from the mold moving speed;
Voltage AC380V(220V),3P,50/60HZ		• Cooling temp. at -15~-18 degree (varies from the environment)
Weight 470KG		

1.3. Lipstick Releasing Machine GETM-4		
BASIC INFORMATION:	CONFIGURATION:	HIGHLIGHTS:
Model GETM-4	PLC: Mitsubishi	• Vacuum releasing
Outer dimension 600x600x1600mm	Touch screen: Wenview	• Lipstick container is lifted up by servo motor, two stage lifting speed.
Power Supply 380V 3P	Sensor: Omron	• precise lifting
Air supply 0.6-0.8Mpa	Conveyor motor: JSCC	
Power 1KW	Cylinder: Airtac	
Speed 3-5 molds/min(acc.to the material and container)	Electric Element: Schneider or equivalent	
	Servo driven lifting: Delta	

GENERAL TERM	
<b>PAKAGING</b>	Non-fumigation plywood case / or pallet
<b>PRODUCTION TIME:</b>	80 working days upon receipt of 40% payment and the necessary samples.
<b>PAYMENT TERM:</b>	This lead time will be confirmed at the order placement.Can vary acc. to our workload.
<b>WARRANTY:</b>	40% by T/T in advance, 60% before shipment.
<b>Offer Validation:</b>	Goods,as built at disposal are guaranteed 12 months. 60 days.

DOCUMENTS PROVIDED	
For each equipment,supplied a technical book in English.	
1	Operation manual for each equipment if it has
2	Installation & Maintenance Instruction for each equipment if it has
3	Electrical Drawing for each equipment if it has
4	Spare parts list for each equipment if it has
5	Qualification Certificate for each equipment if it has

AFTER SALES SERVICES PROVIDED	
1	Free training for customer in GIENI's workshop.
2	Available to send GIENI technician for installation with charging 200USD per day. (NOT AVAILABLE DURING COVID)
3	Available to send GIENI technician for Commissioning with charging 200USD per day. (NOT AVAILABLE DURING COVID)
4	All visa apply, tickets, local accomodation,necessary transportation charge are afforded by customer.
4	Telephone guidance for service will be provided for free in whole life of machine.
5	During Guarantee period,Spare parts is free to replace,exclude wear parts(sealing gasket,piston etc)